

Resistance thermometer

For additional thermowell

Model TR10-B

WIKA data sheet TE 60.02



For further approvals,
see page 19

Applications

- Machine building, plant and vessel construction
- Energy and power plant technology
- Chemical industry
- Food and beverage industry
- Sanitary, heating and air-conditioning technology

Special features

- Sensor ranges from -196 ... +600 °C [-320 ... +1,112 °F]
- For mounting in all standard thermowell designs
- Spring-loaded measuring insert (replaceable)
- Pt100 or Pt1000 sensors
- Explosion-protected versions are available for many approval types



Fig. left: model TR10-B with BSZ connection head

Fig. centre: model TR10-B with 1/4000 connection head

Fig. right: model TR10-B with PIH-L connection head

Description


Resistance thermometers in this model series can be combined with a large number of thermowell / protection tube designs. Operation without thermowell / protection tube is only recommended in certain applications.

A wide variety of possible combinations of Pt100 or Pt1000 sensor, connection head, insertion length, neck length, connection to thermowell / protection tube etc. are available for the thermometers; suitable for any thermowell dimension and any application.

A large number of different explosion-protected approvals are available for the TR10-B.

It is possible to mount analogue or digital WIKA transmitters in the connection head of the TR10-B.

Representation of the components



3160645.09

Legend:






- ① Connection head
- ② Neck tube
- ③ Connection to thermowell / protection tube
- ④ Measuring insert (TR10-A)
- ⑤ Terminal block / Transmitter (option)
- ⑥ Transmitter (option)

Overview of approvals for explosion protection

Approval	Explosion protection				
	Ex i (gas) Zone 0, 1, 2	Ex i (dust) Zone 20, 21, 22	Ex e (gas) Zone 1, 2	Ex t (dust) Zone 21, 22	Ex nA (gas) Zone 2
ATEX	x	x	x	x	x
IECEx	x	x	x	x	x
ECASEx	-	-	x	x	x
EACEx	x	x	x	x	x
Ex Ukraine	x	x	-	-	-
INMETRO	x	x	-	-	-
CCC	x	x	x	x	-
NEPSI	x	x	-	-	-
KCs	x	-	-	-	-
PESO	x	-	-	-	-

→ For further information, see "Approvals" on page 19

Measuring element

Measuring element	
Type of measuring element	Pt100, Pt1000
Measuring current	0.1 ... 1.0 mA
Connection method	
Single elements	Dual elements
1 x 2-wire	
1 x 3-wire	
1 x 4-wire	
2 x 2-wire	
2 x 3-wire	
2 x 4-wire ¹⁾	

Validity limits of the class accuracy in accordance with IEC 60751

Class B ± (0.30 + 0.0050 t) ³⁾	<ul style="list-style-type: none"> ■ -196 ... +600 °C [-321 ... +1112 °F] ■ -196 ... +450 °C [-321 ... +842 °F] ■ -50 ... +500 °C [-58 ... +932 °F] ■ -50 ... +250 °C [-58 ... +482 °F]
Class A ²⁾ ± (0.15 + 0.0020 t) ³⁾	<ul style="list-style-type: none"> -100 ... +450 °C [-148 ... +842 °F] -30 ... +300 °C [-22 ... +572 °F]
Class AA ²⁾ ± (0.10 + 0.0017 t) ³⁾	<ul style="list-style-type: none"> -50 ... +250 °C [-58 ... +482 °F] 0 ... 150 °C [32 ... 302 °F]

1) Not for 3 mm [0.118 in] diameter and 3.2 mm [1/8 in] diameter

2) Not for 2-wire connection method

3) | t | is the numerical value of the temperature in °C without consideration of the sign




→ For further information for Pt100 sensors, see technical information IN 00.17 at www.wika.com.

The table shows the temperature ranges listed in the respective standards, in which the tolerance values (class accuracies) are valid.

- The combinations of a 2-wire connection with class A or class AA are not permissible, since the lead resistance of the MIMS cable and the connection lead negates the higher sensor accuracy.
- Longer probe/cable lengths should be designed with a 4-wire connection, since this connection method has no length effect on the accuracy.
- The use of TR10-B with a Pt100 sensor in a 2-wire connection is technically feasible, of course, but not recommended due to the lead resistance problem.

Connection head

■ European designs per EN 50446 / DIN 43735

Model	Material	Thread size of cable inlet	Ingress protection (max.) 1) 2) IEC/EN 60529	Cap	Surface	Connection to neck tube	
	BSZ	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Spherical hinged cover with cylinder head screw	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSZ-K	Plastic	■ M20 x 1.5 ■ 1/2 NPT	IP65	Spherical hinged cover with cylinder head screw	Black	M24 x 1.5
	BSZ-H	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Raised hinged cover with cylinder head screw	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSZ-H (2 x cable outlet)	Aluminium	■ 2 x M20 x 1.5 ■ 2 x 1/2 NPT	IP65	Raised hinged cover with cylinder head screw	Blue, painted (RAL 5022)	M24 x 1.5
	BSZ-H / DIH10³⁾	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Raised hinged cover with cylinder head screw	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSZ-H / TND⁴⁾	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Raised hinged cover with cylinder head screw	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSZ-HK	Plastic	■ M20 x 1.5 ■ 1/2 NPT	IP65	Raised hinged cover with cylinder head screw	Black	M24 x 1.5
	BS	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Flat cover with 2 screws	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSS	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Spherical hinged cover with clamping lever	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BSS-H	Aluminium	■ M20 x 1.5 ■ 1/2 NPT	IP65	Raised hinged cover with clamping lever	Blue, painted (RAL 5022)	■ M24 x 1.5 ■ 1/2 NPT
	BVS	Stainless steel	M20 x 1.5	IP65	Precision-cast screw-on lid	Natural finish, electropolished	M24 x 1.5

1) IP ingress protection of the connection head The IP ingress protection of the complete TR10-B instrument does not necessarily have to correspond to the connection head.

2) Suitable sealing / cable gland required.

3) LED display DIH10 in combination with transmitter with 4 ... 20 mA output (loop)

4) LC display TND in combination with T38

→ Further thread sizes on request

Model	Explosion protection					
	Without	Ex i (gas) Zone 0, 1, 2	Ex i (dust) Zone 20, 21, 22	Ex e (gas) Zone 1, 2	Ex t (dust) Zone 21, 22	Ex nA (gas) Zone 2
BSZ	X	X	X	X ¹⁾	X ¹⁾	X ²⁾
BSZ-K	X	X	-	-	-	-
BSZ-H	X	X	X	X ¹⁾	X ¹⁾	X ²⁾
BSZ-H (2 x cable outlet)	X	X	X	X ¹⁾	X ¹⁾	X ²⁾
BSZ-H / DIH10³⁾	X	X	-	-	-	-
BSZ-H / TND⁴⁾	X	X	-	-	-	-
BSZ-HK	X	X	-	-	-	-
BS	X	X	X	-	-	-
BSS	X	X	-	-	-	-
BSS-H	X	X	-	-	-	-
BVS	X	X	-	-	-	-

1) Only ATEX and CCC/NEPSI

2) Only ATEX and EACEx

3) LED display DIH10 in combination with transmitter with 4 ... 20 mA output (loop)

4) LC display TND in combination with T38

■ International connection heads

Model	Material	Thread size of cable inlet	Ingress protection (max.) IEC/EN 60529	Cap	Surface	Connection to neck tube	
	KN4-A	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5 	IP65	Screw-on lid	Blue, painted (RAL 5022)	<ul style="list-style-type: none"> ■ M24 x 1.5 ■ 1/2 NPT
	KN4-P ³⁾	Polypropylene	1/2 NPT	IP65	Screw-on lid	White	1/2 NPT
	1/4000	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Blue, painted (RAL 5022)	1/2 NPT
	1/4000	Stainless steel	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Natural finish	1/2 NPT
	7/8000	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Blue, painted (RAL 5022)	1/2 NPT
	7/8000	Stainless steel	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Natural finish	1/2 NPT
	7/8000 / DIH50 ⁴⁾	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Blue, painted (RAL 5022)	1/2 NPT
	7/8000 / DIH50 ⁴⁾	Stainless steel	<ul style="list-style-type: none"> ■ 1/2 NPT ■ 3/4 NPT ■ M20 x 1.5 	IP66	Screw-on lid	Natural finish	1/2 NPT
	PIH-L	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT / closed ■ M20 x 1.5 / closed ■ 2 x 1/2 NPT ■ 2 x M20 x 1.5 	IP66	Screw-on lid, flat	Blue upper body, painted (RAL 5022)	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5
						Grey lower body, painted (RAL 7032)	
	PIH-H	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5 ■ 2 x 1/2 NPT ■ 2 x M20 x 1.5 	IP66	Screw-on lid, high	Blue upper body, painted (RAL 5022)	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5
						Grey lower body, painted (RAL 7032)	
	PIH-W / TND ⁵⁾	Aluminium	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5 ■ 2 x 1/2 NPT ■ 2 x M20 x 1.5 	IP66	Screw-on lid, high	Blue upper body, painted (RAL 5022)	<ul style="list-style-type: none"> ■ 1/2 NPT ■ M20 x 1.5
						Grey lower body, painted (RAL 7032)	

1) IP ingress protection of the connection head The IP ingress protection of the complete TR10-B instrument does not necessarily have to correspond to the connection head.

2) Suitable sealing / cable gland required.

3) On request.

4) LC display DIH50 in combination with transmitter with 4 ... 20 mA output (loop).

5) LC display TND in combination with T38

Model	Explosion protection					
	Without	Ex i (gas) Zone 0, 1, 2	Ex i (dust) Zone 20, 21, 22	Ex e (gas) Zone 1, 2	Ex t (dust) Zone 21, 22	Ex nA (gas) Zone 2
KN4-A	x	x	-	-	-	-
KN4-P¹⁾	x	-	-	-	-	-
1/4000	x	x	x	x	x	x
7/8000	x	x	x	x	x	x
7/8000 / DIH50²⁾	x	x	x	-	-	-
PIH-L / PIH-H	x	x	x	x	x	x
PIH-W / TND³⁾	x	x	x	x	x	x

1) On request

2) LC display DIH50 in combination with transmitter with 4 ... 20 mA output (loop)

3) TND LC display in combination with T38 (Ex e: only zone 2, Ex t: only zone 22)

Connection head with digital display



Connection head BSZ-H with model TND LC display
→ see data sheet TE 38.01



Connection head PIH-W with model TND LC display
→ see data sheets TE 38.01 and AC 80.30



Connection head BSZ-H with model DIH10 LED display
→ see data sheet AC 80.11



Connection head 7/8000 W with model DIH50 LC display
→ see data sheet AC 80.10

For operation of the TND digital display, a model T38 transmitter is always required.

To operate the DIH10 and DIH50 digital displays, a transmitter with a 4 ... 20 mA output is always required.

Cable inlet

Cable inlet	Colour	Ingress protection (max.) IEC/EN 60529 ¹⁾	Thread size of cable inlet	Min./Max. ambient temperature
	Standard cable inlet ²⁾	Natural finish	IP65	M20 x 1.5 -40 ... +80 °C [-40 ... +176 °F]
	Plastic cable gland (cable Ø 6 ... 10 mm) ²⁾	■ Black ■ Grey	IP66	■ M20 x 1.5 ■ 1/2 NPT -40 ... +80 °C [-40 ... +176 °F]
	Plastic cable gland (cable Ø 6 ... 10 mm), Ex e ²⁾	■ Light blue ■ Black	IP66	■ M20 x 1.5 ■ 1/2 NPT ■ -20 ... +80 °C [-4 ... +176 °F] ■ -40 ... +70 °C [-40 ... +158 °F]
	Nickel-plated brass cable gland (cable Ø 6 ... 12 mm)	Natural finish	IP66	■ M20 x 1.5 ■ 1/2 NPT -60 ³⁾ / -40 ... +80 °C [-76 / -40 ... +176 °F]
	Nickel-plated brass cable gland (cable Ø 6 ... 12 mm), Ex e	Natural finish	IP66	■ M20 x 1.5 ■ 1/2 NPT -60 ³⁾ / -40 ... +80 °C [-76 / -40 ... +176 °F]
	Stainless steel cable gland (cable Ø 7 ... 12 mm)	Natural finish	IP66	■ M20 x 1.5 ■ 1/2 NPT -60 ³⁾ / -40 ... +80 °C [-76 / -40 ... +176 °F]
	Stainless steel cable gland (cable Ø 7 ... 12 mm), Ex e	Natural finish	IP66	■ M20 x 1.5 ■ 1/2 NPT -60 ³⁾ / -40 ... +80 °C [-76 / -40 ... +176 °F]
	Plain threaded	-	IP00	■ M20 x 1.5 ■ 1/2 NPT -
	2 x plain threaded ⁵⁾	-	IP00	■ 2 x M20 x 1.5 ■ 2 x 1/2 NPT -
	Built-in connector (male) M12 x 1 (4-pin) Built-in connector (female) M12 x 1 (4-pin)	-	IP65	M20 x 1.5 -40 ... +80 °C [-40 ... +176 °F]
	Sealing plugs for shipping	Transparent	-	■ M20 x 1.5 ■ 1/2 NPT -40 ... +80 °C [-40 ... +176 °F]

1) IP ingress protection of the cable gland. The IP ingress protection of the complete TR10-C instrument does not necessarily have to correspond to the cable gland.

2) Not available for BVS connection head

3) Special version on request (explosion-protected versions only available with specific approvals)

4) Only for BSZ-H connection head

Cable inlet	Explosion protection					
	Without	Ex i (gas) Zone 0, 1, 2	Ex i (dust) Zone 20, 21, 22	Ex e (gas) Zone 1, 2	Ex t (dust) Zone 21, 22	Ex nA (gas) Zone 2
Standard cable inlet ^{1) 3)}	x	x	-	-	-	-
Plastic cable gland ¹⁾	x	x	-	-	-	-
Plastic cable gland (light blue), Ex e ¹⁾	x	x	x	-	-	-
Plastic cable gland (black), Ex e ¹⁾	x	x	x	x	x	x
Brass cable gland, nickel-plated	x	x	x	-	-	-
Brass cable gland, nickel-plated, Ex e	x	x	x	x	x	x
Stainless steel cable gland	x	x	x	-	-	-
Stainless steel cable gland, Ex e	x	x	x	x	x	x
Plain threaded	x	x	x ⁵⁾	x ⁵⁾	x ⁵⁾	x ⁵⁾
2 x plain threaded ²⁾	x	x	x ⁵⁾	x ⁵⁾	x ⁵⁾	x ⁵⁾
Junction box M12 x 1 (4-pin) ³⁾	x	x ⁴⁾	x ⁴⁾	-	-	-
Sealing plugs for shipping	Not applicable, transport protection ⁵⁾					

1) Not available for BVS connection head

2) Only for BSZ-H connection head

3) Not available for 1/2 NPT thread size of cable entry

4) With appropriate mating connector connected

5) Suitable cable gland required for operation

Measuring insert

Measuring insert		
Version	Vibration-resistant mineral-insulated metal-sheathed cable (MIMS cable)	
Optimal heat transfer	Requirement	■ Correct measuring insert length ■ Correct measuring insert diameter
	Bore diameter of the thermowell / protection tube	Max. 1 mm [0.039 in] larger than the measuring insert diameter
	Gap width	With gap widths > 0.5 mm [> 0.020 in] between thermowell / protection tube and measuring insert: → Negative impact on heat transfer → Unfavourable response behaviour of the thermometer
Insertion length	When mounting the measuring insert into a thermowell, it is very important to determine the correct insertion length (= thermowell length for tip thicknesses of ≤ 5.5 mm [≤ 0.217 in]). In order to ensure that the measuring insert is firmly pressed down onto the bottom of the thermowell / protection tube, the insert must be spring-loaded (spring travel: max. 10 mm [0.394 in]).	
Spring travel	Max. 10 mm [0.394 in]	

Measuring insert diameter Ø d in mm [in]	Code number per DIN 43735	Tolerance in mm	Sheath material
3 [0.118]	Standard	3 ^{+0.05} _{-0.05}	■ 1.4571 ■ 316L
6 [0.236]	Standard	6 ⁰ _{-0.1}	
8 [0.315] (6 [0.236] with sleeve)	Standard	8 ⁰ _{-0.1}	■ 1.4571
8 [0.315]	Standard	8 ⁰ _{-0.1}	■ 1.4571 ■ 316L

Transmitter

Transmitter models	Model T15	Model T38
Transmitter data sheet	TE 15.01	TE 38.01
Figure		
Output signal		
4 ... 20 mA	x	x
HART® protocol	-	x
WIKA True Drift Detection	-	x → See data sheet SP 05.26
Connection method	<ul style="list-style-type: none"> ■ 1 x 2-wire ■ 1 x 3-wire ■ 1 x 4-wire 	<ul style="list-style-type: none"> ■ 1 x 2-wire ■ 1 x 3-wire ■ 1 x 4-wire ■ 2 x 2-wire ■ 2 x 3-wire
Measuring current	< 0.2 mA	< 0.33 mA
Explosion protection	Ex version possible	
Mounting types		
Mounting onto the measuring insert	With mounting on the measuring insert, the transmitter replaces the terminal block and is fixed directly to the terminal plate of the measuring insert.	
Mounted within the cover of the connection head	Mounting the transmitter in the cover of the connection head is preferable to mounting it on the measuring insert. With this mounting type, for one, a better thermal insulation is ensured, and in addition, exchange and mounting for servicing is simplified.	



Mounting types

Mounting onto the measuring insert



Measuring insert with mounted transmitter (here: model T32)

Measuring insert prepared for transmitter mounting



Mounted within the cover of the connection head



When using dual sensors in combination with a single transmitter, sensor 1 is connected to the transmitter. The connection leads of sensor 2 (insulated against short-circuits) protrude loosely into the connection head.

Exceptions

- T38: The combination of a 2 x 2-wire or 2 x 3-wire in combination with a T38 transmitter in the “redundancy” configuration.

WIKA True Drift Detection



Special dual sensor functionality

- Special probe (RTD/TC combination, realised in the common probe tip of a measuring insert with 6 mm diameter, in combination with T38 transmitter)
- Permanent monitoring of the resistance sensor by the reference thermocouple
- An incorrect reading can be detected immediately and before the next recalibration. Uncertainties between the calibration intervals are thus eliminated
- Error signalling in accordance with NAMUR NE043, can be configured in accordance with customer specifications
- Individual monitoring of the single measuring locations
- Process optimisation

Possible transmitter mounting positions	Model T15	Model T38
BSZ	○	○
BSZ-K	○	○
BSZ-H	●	●
BSZ-H (2 x cable outlet)	●	●
BSZ-H / DIH10	○	○
BSZ-H / TND	○	○
BSZ-HK	●	●
BS	○	-
BSS	○	○
BSS-H	●	●
BVS	○	○
KN4-A	○	○
KN4-P	○	○
1/4000	○	○
7/8000	○	○
7/8000 / DIH50	○	○
PIH-L / PIH-H	○	○
PIH-W	○	○

Legend:

- Mounted instead of terminal block
- Mounted within the cover of the connection head
- Mounting not possible

The mounting of a transmitter on the measuring insert is possible with all the connection heads listed here. The fitting of a transmitter in the (screw) cap of a connection head is not possible. Mounting of 2 transmitters on request.

For a correct determination of the overall measuring deviation, the sensor and transmitter measuring deviations must be added.

Functional safety with model T38 temperature transmitter



In safety-critical applications, the entire measuring chain must be taken into consideration in terms of the safety parameters. The SIL classification allows the assessment of the risk reduction achieved by the safety installations.

Selected TR10-B resistance thermometers, in conjunction with a suitable temperature transmitter (e.g. model T38, TÜV certified SIL version for protection systems developed in accordance with IEC 61508), are suitable as sensors for safety functions to SIL 2.

For SIL 3 applications, WIKA recommends the use of two individual TR10-B with one SIL-certified T38 transmitter connected to each.

→ For further information, see technical information IN 00.19 on www.wika.com.

Neck tube

Thread sizes				
Neck tube design	Diameter	Thread to the thermowell / protection tube	Connection to head	Materials ¹⁾
Neck tube per DIN 43772	■ 12 x 1.5 mm [0.472 x 0.059 in] ■ 12 x 2.5 mm [0.472 x 0.098 in]	■ G 1/2 B ■ G 3/4 B ■ G 1/4 B ■ M20 x 1.5 ■ M18 x 1.5 ■ M14 x 1.5 ■ 1/2 NPT ■ 3/4 NPT ■ G 1/2 B compression fitting (metal ferrule) ■ G 3/4 B compression fitting (metal ferrule) ■ M18 x 1.5 compression fitting (metal ferrule) ■ M20 x 1.5 compression fitting (metal ferrule) ■ G 1/2 B union nut ■ G 3/4 B union nut ■ M20 x 1.5 union nut ■ G 1/2 B male nut ■ G 3/4 B male nut ■ M20 x 1.5 male nut ■ Without threaded connection, plain	M24 x 1.5 (swivel connection)	1.4571
Neck tube per DIN 43772	14 x 2.5 mm [0.551 x 0.098 in]	■ G 1/2 B ■ G 3/4 B ■ G 1/4 B ■ M20 x 1.5 ■ M18 x 1.5 ■ M14 x 1.5 ■ 1/2 NPT ■ 3/4 NPT ■ G 1/2 B union nut ■ G 3/4 B union nut ■ M20 x 1.5 union nut ■ G 1/2 B male nut ■ G 3/4 B male nut ■ M20 x 1.5 male nut		
Neck tube with counter nut to head	14 x 2.5 mm [0.551 x 0.098 in]	■ 1/2 NPT ■ 3/4 NPT ■ G 1/2 B ■ G 3/4 B ■ G 1/4 B ■ M14 x 1.5 ■ M18 x 1.5 ■ M20 x 1.5	M20 x 1.5 (with counter nut)	1.4571
Double threaded hex bushing (with hexagonal spanner flats)	-	■ G 1/2 B ■ G 3/4 B ■ G 1/4 B ■ 1/2 NPT ■ 3/4 NPT ■ M14 x 1.5 ■ M18 x 1.5 ■ M20 x 1.5	M24 x 1.5, 1/2 NPT	1.4571
“Nipple-union-nipple” neck tube ²⁾	~ 22 mm [~ 0.9 in]	1/2 NPT	1/2 NPT	316
Double threaded hex bushing (tube section)	~ 22 mm [~ 0.9 in]	1/2 NPT	1/2 NPT	316

1) Other materials on request

2) Union material: stainless steel

Neck length		
Neck tube design	Neck length	Min./Max. neck length
Neck tube per DIN 43772	150 mm [~ 6 in]	<ul style="list-style-type: none"> ■ 30 mm [~ 1.2 in] ■ 500 mm [~ 20 in]
Neck tube per DIN 43772, plain	150 mm [~ 6 in]	<ul style="list-style-type: none"> ■ 75 mm [~ 3 in] ■ 900 mm [~ 35 in]
Neck tube with counter nut to head	150 mm [~ 6 in]	<ul style="list-style-type: none"> ■ 75 mm [~ 3 in] ■ 250 mm [~ 10 in]
Double threaded hex bushing (with hexagonal spanner flats)		
M24 x 1.5 to connection head, parallel thread to thermowell / protection tube	13 mm [0.512 in]	-
½ NPT to connection head, parallel thread to thermowell / protection tube	~ 25 mm [1 in]	-
M24 x 1.5 to connection head, tapered thread to thermowell / protection tube	~ 25 mm [1 in]	-
½ NPT to connection head, tapered thread to thermowell / protection tube	~ 25 mm [1 in]	-
“Nipple-union-nipple” neck tube	~ 150 mm [6 in]	<ul style="list-style-type: none"> ■ ~ 75 mm [3 in] ■ ~ 250 mm [10 in]
Double threaded hex bushing (tube section)	~ 50 mm [2 in]	<ul style="list-style-type: none"> ■ ~ 50 mm [2 in] ■ ~ 250 mm [10 in]

The neck tube is screwed into the connection head. The neck length depends on the intended use. Usually, an isolation is bridged by the neck tube. Also, in many cases, the neck tube serves as a cooling element between the connection head and the medium, in order to protect a possible built-in transmitter from high medium temperatures.

→ Other versions on request.

Operating conditions

Operating conditions	
Ambient and storage temperature	<ul style="list-style-type: none"> ■ -40 ... +80 °C [-40 ... +176 °F] ■ -60¹⁾ ... +80 °C [-76 ... +176 °F]
Vibration resistance	The information on vibration resistance refers to the tip of the measuring insert.

1) Special version on request (explosion-protected versions only available with specific approvals)

Examples of vibration resistance

	Measuring insert Ø 6 mm [0.236 in]	Measuring insert Ø 3 mm [0.118 in]
Thermometer version		
Sensor	<ul style="list-style-type: none"> ■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film) 	<ul style="list-style-type: none"> ■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)
Connection method	<ul style="list-style-type: none"> ■ 3-wire ■ 4-wire 	<ul style="list-style-type: none"> ■ 3-wire ■ 4-wire (only 1 x Pt100)
Diameter	Ø 6 mm [0.236 in]	Ø 3 mm [0.118 in]
Insertion length (A) + neck length (N)	100 ... 1,100 mm [~ 4 ... 43 in]	100 ... 1,100 mm [~ 4 ... 43 in]
Material	<ul style="list-style-type: none"> ■ Stainless steel 1.4571 ■ Stainless steel 316L 	<ul style="list-style-type: none"> ■ Stainless steel 1.4571 ■ Stainless steel 316L
Vibration resistance		
Standard probe tip, (max. 3g amplitude / 6g peak-to-peak)	x	x
Vibration-resistant probe tip (max. 10g amplitude / 20g peak-to-peak)	x	x
Highly vibration-resistant probe tip (max. 25g amplitude / 50g peak-to-peak)	x	x
Extremely vibration-resistant probe tip (max. 50g amplitude / 100g peak-to-peak)	x	-

The thermometer designs listed above describe instruments in standard designs.

Testing of the vibration resistance per IEC 60068-2-6. Vibration resistance of thermometers in other configurations as well as vibration resistance higher than 50g amplitude / 100g peak-to-peak on request.

IP ingress protection per IEC/EN 60529

First numeral	Degree of protection / Short description	Test parameters
Degrees of protection against solid foreign bodies (defined by the 1st numeral)		
5	Dust-protected	Per IEC/EN 60529
6	Dust-tight	Per IEC/EN 60529
Degrees of protection against water (defined by the 2nd numeral)		
4	Protected against splash water	Per IEC/EN 60529
5	Protected against water jets	Per IEC/EN 60529
6	Protected against powerful water jets	Per IEC/EN 60529

Standard ingress protection of model TR10-B is IP65.


The specified degrees of protection apply under the following conditions:

- Use of a suitable thermowell / protection tube (without suitable thermowell / protection tube: IP40)
- Use of a suitable cable gland
- Use of a cable cross-section appropriate for the gland or select the appropriate cable gland for the available cable
- Adhere to the tightening torques for all threaded connections

→ For further information, see technical information IN 00.64 at www.wika.com

Sealing at the connection head

A ring-shaped seal in the cover of the connection head and a suitable cable gland prevent the ingress of dust and water.



Sealing at the junction of the protection tube / neck tube to the connection head

The thermowell / protection tube is screwed to the connection head or neck tube, which means that IP65 ingress protection is usually achieved without any problems. A suitable ring-shaped seal and, if necessary, PTFE sealing tape are used.



Examples of response time for measuring insert

	Measuring insert Ø 6 mm [0.236 in]	Measuring insert Ø 3 mm [0.118 in]
Thermometer version		
Sensor	■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)	■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)
Connection method	■ 3-wire ■ 4-wire	■ 3-wire ■ 4-wire (only 1 x Pt100)
Diameter	6 mm [0.236 in]	Ø 3 mm [0.118 in]
Insertion length (A) + neck length (N)	100 ... 1,100 mm [4 ... 43 in]	100 ... 1,100 mm [4 ... 43 in]
Material	■ Stainless steel 1.4571 ■ Stainless steel 316L	■ Stainless steel 1.4571 ■ Stainless steel 316L
Response time in seconds (+/- 10 %)		
$t_{0.5}$	3.8	2.8
$t_{0.63}$	4.8	3.5
$t_{0.9}$	8.6	6.6

Example for the response time of the complete instrument with bar stock material thermowell

	TW10 Flanged thermowell	TW25 Weld-in thermowell	TW55 Weld-in thermowell (DIN 43772)
Thermometer version			
Sensor	■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)	■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)	■ 1 x Pt100 (thin film) ■ 2 x Pt100 (thin film)
Connection method	■ 3-wire ■ 4-wire	■ 3-wire ■ 4-wire	■ 3-wire ■ 4-wire (only 1 x Pt100)
Thermowell / Protection tube	TW10, tapered, 12.7/20.0 mm	TW25-B, straight, 27.0 mm	TW55-6 form 4, 12.5/24.0 mm
Bore / Tip thickness	6.6 mm / 6.4 mm [0.26 in / 0.25 in]	6.6 mm / 6.4 mm [0.26 in / 0.25 in]	7.0 mm / min. 4 mm
Diameter	Ø 6 mm [0.236 in]	Ø 6 mm [0.236 in]	Ø 6 mm [0.236 in]
Insertion length U	175 mm [approx. 7 in]	250 mm [approx. 10 in]	65 mm (L = 200 mm)
Material	Stainless steel 316L	Stainless steel 316L	Stainless steel 316L
Response time in seconds (+/- 10 %)			
$t_{0.5}$	28	26	33
$t_{0.63}$	36	33	45
$t_{0.9}$	80	68	114

Immersion depth during measurement: approx. 125 mm

Fundamentals of measurements:

VDI/VDE directive 3522 part 1: Dynamic behaviour of contact thermometers / Principles and characteristic values

VDI/VDE directive 3522 part 2 Dynamic behaviour of contact thermometers / Experimental determination of time percentage values


IEC 60751 Definition of thermal response time / Specification of measurement parameters

IEC 60751 Thermal response time

Medium: water

→ Further response times of thermometers in other dimensions, configurations or materials on request.

Thermowell / Protection tube

Thermowell / Protection tube selection		
Representation	Model	Data sheet
	TW10	<ul style="list-style-type: none"> ■ TW 95.10 ■ TW 95.11 ■ TW 95.12
	TW15	TW 95.15
	TW20	TW 95.20
	TW25	TW 95.25
	TW30	TW 95.30
	TW45	TW 95.45
	TW50	TW 95.50
	TW55	TW 95.55

→ Further special thermowells on request.

Approvals

Approvals included in the scope of delivery

Logo	Description	Country
	EU declaration of conformity	European Union
	EMC Directive ¹⁾	
	EN 61326 emission (group 1, class B) and immunity (industrial application)	
	RoHS directive	

1) Only for built-in transmitter

Optional approvals

Logo	Description	Country
	<p>DNV GL Type approval for the shipbuilding industry - Maximum insertion length l_1: 435 mm - Connection head: model BSZ - Neck tube: $\varnothing 11 \times 2$ mm or $\varnothing 12 \times 2.5$ mm, max. 150 mm long - Measuring insert: $\varnothing 6$ mm - Optional with TW10-P (see data sheets TW 95.10, TW 95.12)</p> <p>Location classification:</p> <p>Temperature D (ambient temperature: -25 ... +70 °C)</p> <p>Humidity B (relative humidity: up to 100 %)</p> <p>Vibration B (frequency: 3 ... 25 Hz; amplitude: 1.6 mm peak; frequency: 25 ... 100 Hz; amplitude: 4 g)</p> <p>EMC Not relevant</p> <p>Case Required protection in accordance with DNV rules shall be provided upon installation on board. For use on open deck a connection head with IP68 is required.⁶⁾ (for "open deck")</p>	International

1) Only for connection head model BSZ, BSZ-H, 1/4000, 5/6000, 7/8000 or PI housing, see "Connection head"

2) Only for connection head, model 1/4000, 5/6000, 7/8000 or PI housing, see "Connection head"

3) Only without transmitter

4) Only with transmitter

5) Only for connection head, model 1/4000, 5/6000, 7/8000, BSZ-H or PI housing, see "Connection head"

6) Suitable cable gland required

Instruments marked with "ia" may also be used in areas only requiring instruments marked with "ib" or "ic". If an instrument with "ia" marking has been used in an area with requirements in accordance with "ib" or "ic", it can no longer be operated in areas with requirements in accordance with "ia" afterwards.

The permissible power, P_{max} , as well as the permissible ambient temperature, for the respective category can be seen on the Ex certificate or the operating instructions.

The transmitters have their own certificates for hazardous areas. The permissible ambient temperature ranges of the built-in transmitters can be taken from the corresponding transmitter operating instructions and approvals.

Manufacturer's declaration

Logo	Description
	<p>SIL 2 For SIL 3, see page 12 Functional safety</p>
	<p>NAMUR NE 024 Hazardous areas (Ex i)</p>

Certificates

Certification type	Measurement accuracy	Material certificate ¹⁾
2.2 test report	x	x
3.1 inspection certificate	x	x
DAkkS calibration certificate	x	-

1) Thermowells / Protection tubes have their own material certificates for selected components


For calibration, the measuring insert is removed from the thermometer. The minimum length (metal part of the probe) for carrying out a 3.1 measurement accuracy test or DAkkS is 100 mm [~ 4 in].

Calibration of shorter lengths as well as calibration of versions in 2-wire connection possible on request.


The different certifications can be combined with each other.

→ For approvals and certificates, see website


Dimensions in mm [in]



The following figures show examples of connection heads.



Neck tube per DIN 43772, plain, with/without compression fitting



Legend:

A (l₁) Insertion length (parallel threads)

A (l₂) Insertion length (tapered threads)

l₅ Measuring insert length

N (M_H) Neck length

K_E 1/2 NPT: 8.13 mm [0.320 in]

3/4 NPT: 8.61 mm [0.339 in]


C_T Thread of cable inlet

Ø F₁ Neck tube diameter


P Thread to the thermowell / protection tube




Ø d Measuring insert diameter

Neck tube, with counter nut to head



Double threaded hex bushing (with hexagonal spanner flats)





Legend:

A (l_1) Insertion length (parallel threads)
 A (U_2) Insertion length (tapered threads)
 l_5 Measuring insert length
 N (M_H) Neck length
 K_E $\frac{1}{2}$ NPT: 8.13 mm [0.320 in]
 $\frac{3}{4}$ NPT: 8.61 mm [0.339 in]

C_T Thread of cable inlet
 $\varnothing F_1$ Neck tube diameter
 P Thread to the thermowell / protection tube
 $\varnothing d$ Measuring insert diameter

Standard article



Configurator



© 04/2003 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.

The specifications given in this document represent the state of engineering at the time of publishing.

We reserve the right to make modifications to the specifications and materials.

In case of a different interpretation of the translated and the English data sheet, the English wording shall prevail.

