

# Rosemount™ 4051S Pressure Transmitter



## Revolutionize how you measure pressure

With innovative features to make tasks easier, the Rosemount 4051S Pressure Transmitter gives you more—more flexibility, more performance, more insights, and more peace of mind. Emerson has designed the 4051S to simplify your day-to-day operations and help you spend less time configuring your pressure transmitter and more time focusing on the tasks that matter. The 4051S Pressure Transmitter is built to withstand the toughest processes and the harshest environments with safety built-in at its core.

---

**Contents**

Overview..... 2

Rosemount 4051S Coplanar™ Pressure Transmitter..... 7

Rosemount 4051S In-line Pressure Transmitter..... 18

Rosemount 4051SF Differential Pressure Flow Meters..... 26

Rosemount 4051SLT Level Transmitter..... 55

Specifications..... 73

## Overview

The 4051S Pressure Transmitter is built to withstand the toughest processes and the harshest environments. Users get more peace of mind knowing it will perform day after day with:

- Industry-leading 20-year warranty
- Industry-leading 20-year stability
- 40 ms time response option
- 800:1 rangedown reduces the number of unique models you need to stock.

## Designed to simplify your day-to-day operations

### Easier to use

Designed to simplify your day-to-day operations, the Rosemount 4051S Pressure Transmitter can help you spend less time configuring your pressure transmitter and more time focusing on the tasks that matter.

- Graphical, backlit display is larger, easier to read, and available in seven languages.
- Intuitive user interface, so it is easy to find what you are looking for.
- Simplify configuration and maintenance with Bluetooth® connectivity.
- Easily configure for level, volume, flow, or totalized flow in just a few clicks.



### Advanced safety features

The 4051S Pressure Transmitter has safety built-in at its core with more ways to help keep your team and facility safe.

- Increase personnel safety and avoid entering hazardous locations with Bluetooth connectivity.
- Built-in proof testing provides reliable verification of instrument functionality to improve operational efficiency and safety.

### More insights

With more information at your fingertips, you can make more confident decisions.

- **Loop Integrity** diagnostic continuously monitors the health of the entire electrical loop to detect potential failures before they disrupt your operations.
- Ensure your output responds to process changes with **Plugged Impulse Line** detection.
- Detect abnormal conditions with process intelligence and get early visibility to potential process disruptions.
- Prioritize work and avoid shutdowns with process alerts.
- Built-in calibration and diagnostic logs give you access to information when you need it.



---

### Greater connectivity

Get connected with Bluetooth technology to enable increased productivity, reliability, and safety. Make real-time decisions with:

- Simplified operator rounds through fast and easy device connection.
- Enhanced troubleshooting and configuration by knowing which devices need attention.
- AMS Device Configurator application for a seamless experience across devices.



---

### Reliable relay switches

Pressure switches provide enhanced asset protection and maintain system safety.

- Reduce accuracy and reliability issues that can happen with standalone switches.
- Enable discrete control capabilities for installations without a programmable logic controller (PLC) or distributed control system (DCS).
- Control equipment based on pressure, flow, or level variables and know your switch is correctly configured and functioning correctly.
- Safety Instrumented Systems (SIS) applications provide redundant SIS path to final control element.

## Rosemount 4051S Series selection guide

For the latest information on product availability and/or options, use the product configurator at [Emerson.com/global](https://www.emerson.com/global) or contact your local Emerson representative.

### Rosemount 4051S Pressure Transmitter



The Rosemount 4051S Pressure Transmitter offers superior accuracy, minimal maintenance, and exceptional durability, making it a trusted choice for reliable and precise pressure measurement solutions.

- Ideal for gauge, absolute, and differential pressure applications requiring a manifold, flange, or direct process connection.
- Rosemount R305 and R306 Instrument Manifolds seamlessly integrate within the Rosemount 4051S model number.

Ordering information:

[Rosemount 4051S Coplanar™ Pressure Transmitter](#)

[Rosemount 4051S In-line Pressure Transmitter](#)

### Rosemount 4051SLT Pressure Transmitter



Emerson's diverse remote seal offering combined with the Rosemount 4051S transmitter makes the 4051SLT Level Transmitter capable of tackling the most demanding applications.

- Ideal for pressurized and vented tank level measurement applications.
- Designed for direct mounting, remote mounting, balanced systems, and Tuned-System™ assemblies.
- Welded-repairable construction allows the seal system to be repaired.
- Use the [Sizing & Selection tool](#) to find the best solution for your application.

**Rosemount 4051SF Differential Pressure Flow Meters**

4051SF Differential Pressure Flow Meters are built on the reliable 4051S platform, offering a versatile solution for flow measurement.

- Designed for accurate and reliable flow measurement, ensuring optimal performance in various process conditions.
- Arrives fully-configured, leak-tested, and ready-to-install right out of the box for fast installation.
- [DP Flow Sizing & Selection Tool](#) streamlines the configuration process, considering factors like accuracy, pressure loss, and installation requirements.
- Use the sizing tool to find the best solution for your application.

# Rosemount 4051S Coplanar™ Pressure Transmitter



4051S Coplanar Pressure Transmitters are the industry leader for differential, gauge, and absolute pressure measurement. The Coplanar platform allows seamless integration with manifolds, primary elements, and seal solutions. Capabilities include:

- Ultra, Ultra-For-Flow, and Classic performance
- 4–20 mA HART® protocol with two integral relay switches
- Safety certification (Option code QT)
- Advanced diagnostics
- Remote display and interface

[VIEW PRODUCT >](#)

[CONFIGURE >](#)

## Online product configurator

Many products are configurable online using our product configurator.

Select the **Configure** button or visit [Emerson.com/global](https://emerson.com/global) to start. With this tool's built-in logic and continuous validation, you can configure your products more quickly and accurately.

## Specifications and options

The purchaser of the equipment must specify and select:

- Product materials
- Options
- Components

## Optimizing lead time

The starred offerings (★) represent the most common options and should be selected for the fastest delivery. The non-starred offerings are subject to additional delivery lead time.

## Required model components

### Model

Code	Description	
4051S	Pressure transmitter	★

## Measurement functionality

Code	Description	
1	Pressure, level	★

## Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

## Performance class

Code	Description	
1	Ultra: 0.025% span accuracy, 200:1 rangedown, 20-year stability, 20-year limited warranty	★
2 <sup>(1)</sup>	Ultra-For-Flow: 0.04% reading accuracy, 200:1 turndown, 20-year stability, 20-year limited warranty	★
4	Classic: 0.035% span accuracy, 150:1 rangedown, 20-year stability	★

(1) This option is only available with pressure measurement type CD, pressure range codes 2 and 3, 316L Stainless steel (SST) or Alloy C-276 isolating diaphragm and silicone fill fluid.

## Pressure measurement and module type

Code	Description	
CD	Differential pressure, Coplanar™	★
CG	Gauge pressure, Coplanar	★
CA	Absolute pressure, Coplanar	★

## Pressure range

Code	Description			
	Differential pressure	Gauge pressure	Absolute pressure	
U <sup>(1)</sup>	Universal 800:1 range: -1,000 to 1,000 inH <sub>2</sub> O (-2.49 to 2.49 bar)	Universal 800:1 range: -1,000 to 1,000 inH <sub>2</sub> O (-2.49 to 2.49 bar)	N/A	★
0 <sup>(2)</sup>	-3 to 3 inH <sub>2</sub> O (-7.47 to 7.47 mbar)	N/A	0 to 5 psia (0 to 0.34 bar)	★
1	-25 to 25 inH <sub>2</sub> O (-62.16 to 62.16 mbar)	-25 to 25 inH <sub>2</sub> O (-62.16 to 62.16 mbar)	0 to 30 psia (0 to 2.07 bar)	★
2	-250 to 250 inH <sub>2</sub> O (-621.60 to 621.60 mbar)	-250 to 250 inH <sub>2</sub> O (-621.60 to 621.60 mbar)	0 to 150 psia (0 to 10.34 bar)	★
3	-1,000 to 1000 inH <sub>2</sub> O (-2.49 to 2.49 bar)	-393 to 1,000 inH <sub>2</sub> O (-0.97 to 2.49 bar)	0 to 800 psia (0 to 55.16 bar)	★
4	-300 to 300 psi (-20.68 to 20.68 bar)	-14.2 to 300 psig (-0.97 to 20.68 bar)	0 to 4,000 psia (0 to 275.79 bar)	★

Code	Description			
5	-2,000 to 2,000 psi (-137.89 to 137.89 bar)	-14.2 to 2,000 psig (-0.97 to 137.89 bar)	N/A	★

- (1) Universal range option is only available with diagnostic code A (loop integrity will be disabled).
- (2) Pressure range code 0 is only available with SST traditional flange, 316L Stainless steel (SST) diaphragm material, glass-filled PTFE O-ring (standard), and bolting option L4.

### Isolating diaphragm material

Code	Description	
2 <sup>(1)</sup>	316L stainless steel (SST)	★
3 <sup>(1)</sup>	Alloy C-276	★
4 <sup>(1)</sup>	Alloy 400	
5 <sup>(2)</sup>	Tantalum	
6 <sup>(1)(3)</sup>	Gold-plated Alloy 400	
7 <sup>(1)</sup>	Gold-plated 316L SST	

- (1) Materials of construction comply with metallurgical requirements highlighted within NACE<sup>®</sup> MR0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments. Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.
- (2) Tantalum is not available with pressure range 1 and Q15.
- (3) Includes a graphite-filled PTFE O-ring.

### Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

### Process connection type

Code	Description	
A	Integral manifold	★
G	Transmitter flange with assembled manifold	★
F	Transmitter flange	★
L	Level flange	★

### Process connection style, size, and valve configuration

To select a process connection style, find the column that matches the chosen process connection type and then select the corresponding code.

Code	Description				
	Process connection type A: Integral manifold	Process connection type G: Transmitter flange with assembled manifold	Process connection type F: Transmitter flange	Process connection type L: Level flange	
01	R305, Coplanar™ ½-14 NPT female 2-valve	Coplanar flange Traditional manifold (0304 specified separately)	Coplanar flange ¼ NPT	2 in. ANSI Class 150	★

Code	Description				
	Process connection type A: Integral manifold	Process connection type G: Transmitter flange with assembled manifold	Process connection type F: Transmitter flange	Process connection type L: Level flange	
02	R305, Coplanar ½-14 NPT female 3-valve	Traditional flange Traditional manifold (0304 specified separately)	Traditional flange ¼ NPT	2 in. ANSI Class 300	★
03	R305, Coplanar ½-14 NPT female 5-valve	DIN-Traditional flange Traditional manifold (0304 specified separately)	DIN-compliant traditional flange ¼ NPT	3 in. ANSI Class 150	★
04	Alternative Rosemount manifold (specified separately)	Coplanar flange 3rd party manifold (specified separately)	Bottom vent traditional flange ¼ NPT	3 in. ANSI Class 300	★
05	Alternative 3rd party manifold (specified separately)	Traditional flange 3rd party manifold (specified separately)	Coplanar flange RC ¼	DIN DN 50 PN 40	★
06	N/A	DIN-Traditional flange 3rd party manifold (specified separately)	Traditional flange RC ¼	DIN DN 80 PN 40	★
07	N/A	N/A	Bottom vent traditional flange RC ¼	N/A	★

### Process connection material

To select a process connection material, find the column that matches the chosen process connection type and style and then select the corresponding code.

Code	Description					
	Process connection type A: Integral manifold	Process connection type G: Transmitter flange with assembled manifold	Process connection type F: Transmitter flange		Process connection type L: Level flange	
	Manifold body   Valve packing	Flange body   Drain/ vent valve	Process connection style (01, 02, 04, 05, 06, 07)	Process connection style (03)	Flange body   Drain/vent valve	
Flange body   Drain/vent valve			Flange body   Drain/vent valve   Bolting	Flange body   Drain/vent valve		
N	Specified in separate model number	N/A	N/A	N/A	N/A	★
A	All 316/316L SST   PTFE	Stainless steel (SST)   316 SST	SST   316 SST	SST   316 SST   7/16 in.	SST   316 SST	★
B	All 316/316L SST   Graphite-based	SST   C-276	SST   C-276 <sup>(1)</sup>	SST   316 SST   M10	SST   C-276	★
C	N/A	Alloy C-276   C-276	Alloy C-276   C-276 <sup>(1)</sup>	SST   316 SST   M12	Alloy C-276   C-276	★
E	N/A	CS   316 SST	CS   316 SST	N/A	N/A	★
F	N/A	CS   C-276	CS   C-276 <sup>(1)</sup>	N/A	N/A	★

Code	Description					
	Process connection type A: Integral manifold	Process connection type G: Transmitter flange with assembled manifold	Process connection type F: Transmitter flange		Process connection type L: Level flange	
	Manifold body   Valve packing	Flange body   Drain/vent valve	Process connection style (01, 02, 04, 05, 06, 07)	Process connection style (03)	Flange body   Drain/vent valve	
			Flange body   Drain/vent valve	Flange body   Drain/vent valve   Bolting		
G	N/A	Alloy 400   Alloy 400/K-500	Alloy 400   Alloy 400/K-500	N/A	N/A	

(1) *Materials of Construction comply with metallurgical requirements highlighted within NACE® MR0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments. Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.*

## Transmitter housing material

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

## Housing conduit/cable threads

Code	Description	
1	½–14 NPT	★
2	M20 x 1.5	★
3 <sup>(1)</sup>	G½	★

(1) *Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.*

## Transmitter output

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

## Additional options

### Local wireless device access

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

## Display type

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

## Electronic cabling (for remote display)

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★
RQ	100 ft. (30.5 m) of cable (blue color)	★

## Maximum static line pressure

Code	Description	
P0 <sup>(1)</sup>	6,170 psig (425 bar) static pressure limit	★

(1) Requires 316L SST, Alloy C-276, or Gold-plated 316L Stainless steel (SST) diaphragm material, assemble to Rosemount 305 integral manifold or DIN-compliant traditional flange process connection, and bolting option L7 or L8. Limited to Pressure Range (Differential), ranges 2– 5.

## Transmitter time response

Code	Description	
P6 <sup>(1)</sup>	High-speed sensor time response	★

(1) Only available with differential pressure range 2 or 3 and diagnostics option A (**Loop Integrity** diagnostic will be disabled).

## Bracket type, bracket material, and bolt material

Code	Description			
	Bracket type	Bracket material	Bolt material	
B4	Coplanar™ flange bracket for 2-in. pipe and panel	304 Stainless steel (SST)	300 SST	★
BE	Coplanar flange bracket for 2-in. pipe and panel	316 SST	316 SST	★
B1	Traditional flange bracket for 2-in. pipe mount	Carbon steel	Carbon steel	★
B2	Traditional flange bracket for panel mount	Carbon steel	Carbon steel	★
B3	Traditional flange flat bracket for 2-in. pipe mount	Carbon steel	Carbon steel	★
B7	Traditional flange bracket for 2-in. pipe mount	Carbon steel	316 SST	★
B8	Traditional flange bracket for panel mount	Carbon steel	316 SST	★
B9	Traditional flange flat bracket for 2-in. pipe mount	Carbon steel	316 SST	★

Code	Description			
	Bracket type	Bracket material	Bolt material	
BA	Traditional flange bracket for 2-in. pipe mount	316 SST	316 SST	★
BC	Traditional flange flat bracket for 2-in. pipe mount	316 SST	316 SST	★
BD	Vertical mount bracket	316 SST	300 SST	★
BF <sup>(1)</sup>	AGCO bracket	316 SST	300 SST	★
BG <sup>(1)</sup>	AGCO bracket	316 SST	316 SST	★

(1) Options BF and BG are only available with process connection type A and process connection style 01, 02, or 03.

## Tagging and fastener material

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

## RFID tagging

Code	Description	
Y3	RFID tag	★

## Bolting material

Code	Description	
L4	Austenitic 316 stainless steel (SST) bolts	★
L5	ASTM A193, Grade B7M bolts	★
L6	Alloy K-500 bolts	★
L7 <sup>(1)</sup>	ASTM A453, Class D, Grade 660 bolts	★
L8	ASTM A193, Class 2, Grade B8M bolts	★
L9	ASTM A193, Class 2, B8M, socket head bolts	

(1) Bolts are not considered process-wetted. In instances where NACE MR0175/International Organization for Standardization (ISO) 15156 and NACE<sup>®</sup> MR0103 conformance is required for bolting, L7 is the recommended bolting option.

## Transient protection

Code	Description	
T1	Transient terminal block	★

## Extended product warranty

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

## Pressure testing

Code	Description
P1	Hydrostatic testing with certificate

## Special cleaning

This is not available with graphite O-ring material, option code L2 or L3. Also, not available with graphite manifold valve packing.

Code	Description
P2	Cleaning for special services
P3	Cleaning for special services with testing for <1 ppm chlorine/fluorine

## Software configuration

Code	Description
C1	Custom software configuration (requires Configuration Data Sheet) ★

## Alarm limit

Code	Description
C4	NAMUR alarm and saturation levels, high alarm ★
C5	NAMUR alarm and saturation levels, low alarm ★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm ★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm ★
C8	Low alarm (standard Rosemount alarm and saturation levels) ★

<sup>(1)</sup> Options C6 and C7 require C1 and a Configuration Data Sheet.

## Flange adapter

The flange adapter material will match the material selected in the process connection size.

Code	Description
D2	Flange adapter(s) ★

## Ground screw

Code	Description
X1	External ground screw assembly ★

## Drain/vent valve

Code	Description
D5	Remove transmitter drain/vent valves and install plugs ★
D7	Stainless steel (SST) Coplanar™ flange without drain/vent ports ★
D8	Ceramic drain/vent valves ★

Code	Description	
DC	Traditional flange-ports left open	★

### Additional drain/vent options

This option is only available with process connection type A and process connection style 01, 02, or 03.

Code	Description	
DM	Drain/vent plug, same as manifold body material	★

### Sensor fill fluid

Only available on differential and gauge measurement types. Silicone fill fluid is standard.

Code	Description	
L1	Inert sensor fill fluid	★

### O-ring

Glass-filled PTFE O-ring is standard.

Code	Description	
L2	Graphite-filled PTFE O-ring	★
L3	All graphite gasket	★

### Conduit plug

Transmitter is shipped with 316 Stainless steel (SST) conduit plug (uninstalled) in place of standard aluminum conduit plug.

Code	Description	
DO	316 SST conduit plug	★

### Conduit electrical connector

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

### Cold temperature

This is only available on pressure ranges 1–5, with silicone sensor fill fluid and stainless steel (SST) or Alloy C-276 isolating diaphragms and classic performance.

Code	Description	
BR5	-58 °F (-50 °C) cold temperature operation	★
BR6	-76 °F (-60 °C) cold temperature operation	★

### Process wetted thread sealant

Code	Description	
Z1	High temperature liquid thread sealant [-65 °F to 400 °F (-54 °C to 204 °C) temperature rating]	★
Z2	Liquid thread sealant [-63 °F to 302 °F (-53 °C to 150 °C) temperature rating]	★
Z3	Anaerobic PTFE paste	★
Z4	GraFoil® thread sealant	★
Z5	Loctite® 580 thread sealant	★

### Custody transfer

Code	Description	
D3	Measurement Canada accuracy approval	★

### Drinking water approval

Code	Description	
DW	NSF drinking water approval	★

### Shipboard approvals

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

### Calibration certification

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

### Material traceability certification

Code	Description	
Q8	Material traceability certification per EN 10204 3.1	★

### Positive material identification (PMI)

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

## Quality certification for safety

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

## NACE® certificate

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

## Material recommendation for NACE®

This option is only available with process connection type A and process connection style 01, 02, or 03.

Code	Description	
SG	Sour gas (meets NACE MR0175/ISO 15156, MR0103/International Organization for Standardization (ISO) 17945)	★

## Product certifications

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

# Rosemount 4051S In-line Pressure Transmitter



Rosemount 4051S In-line Pressure Transmitters are the industry leader for gauge and absolute pressure measurement. The in-line, compact design allows the transmitter to be connected directly to a process for quick, easy, and cost effective installation. Capabilities include:

- Ultra and Classic performance
- 4–20 mA HART® protocol with two integral relay switches
- Safety certification (Option code QT)
- Advanced diagnostics
- Remote display and interface

[VIEW PRODUCT >](#)

[CONFIGURE >](#)

## Online product configurator

Many products are configurable online using our product configurator.

Select the **Configure** button or visit [Emerson.com/global](https://emerson.com/global) to start. With this tool's built-in logic and continuous validation, you can configure your products more quickly and accurately.

## Specifications and options

The purchaser of the equipment must specify and select:

- Product materials
- Options
- Components

## Optimizing lead time

The starred offerings (★) represent the most common options and should be selected for the fastest delivery. The non-starred offerings are subject to additional delivery lead time.

## Required model components

### Model

Code	Description	
4051S	Pressure transmitter	★

### Measurement functionality

Code	Description	
1	Pressure, level	★

### Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

### Performance class

Code	Description	
1	Ultra: 0.025% span accuracy, 200:1 rangedown, 20-year stability, 20-year limited warranty	★
4	Classic: 0.035% span accuracy, 150:1 rangedown, 20-year stability	★

### Pressure measurement

Code	Description	
TG	Gauge pressure, In-line	★
TA	Absolute pressure, In-line	★

### Pressure range

Code	Description		
	Gauge pressure	Absolute pressure	
1	-14.7 to 30 psig (-1.01 to 2.06 bar)	0 to 30 psia (0 to 2.06 bar)	★
2	-14.7 to 150 psig (-1.01 to 10.34 bar)	0 to 150 psia (0 to 10.34 bar)	★
3	-14.7 to 800 psig (-1.01 to 55.15 bar)	0 to 800 psia (0 to 55.15 bar)	★
4	-14.7 to 4,000 psig (-1.01 to 275.79 bar)	0 to 4,000 psia (0 to 275.79 bar)	★
5	-14.7 to 10,000 psig (-1.01 to 689.47 bar)	0 to 10,000 psia (0 to 689.47 bar)	★

### Isolating diaphragm material

Code	Description	
2	316L Stainless steel (SST)	★
3	Alloy C-276	★

### Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

## Process connection type

Code	Description	
A	Integral manifold	★
T	In-line direct connection	★

## Process connection style, size, and valve configuration

To select a process connection style, find the column that matches the chosen process connection type and then select the corresponding code.

Code	Description		
	Integral manifold	In-line direct connection	
01	R306, In-line, ½-14 NPT female, 2-valve	½-14 NPT female	★
02	R306, In-line, ½-14 NPT male, 2-valve	Non-threaded instrument flange (I-flange)	★
03	R306, In-line, ¾-14 NPT male, 2-valve	G½ A DIN 16288 male	★
04	R306, In-line, ½-14 NPT male, block and bleed	Coned and threaded, compatible and autoclave type F-250-C (absolute pressure, range 5 only)	★
05	Alternative Rosemount manifold (specified separately)	N/A	★
06	Alternative third party manifold (specified separately) with ½-14 NPT female	N/A	★
07	Alternative third party manifold (specified separately) with G½ A DIN 16288 male	N/A	★

## Process connection material

To select a process connection material, find the column that matches the chosen process connection type and style and then select the corresponding code.

Code	Description		
	Integral manifold	In-line direct connection	
	Manifold body   Valve packing		
N	Specified in separate model number	N/A	★
A	All 316/316L Stainless steel (SST)   PTFE	Material will match transmitter isolating diaphragm.	★
B	All 316/316L SST   Graphite-based	N/A	★

## Transmitter housing material

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

## Housing conduit/cable threads

Code	Description	
1	½-14 NPT	★
2	M20 x 1.5	★

Code	Description	
3 <sup>(1)</sup>	G½	★

(1) Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.

## Transmitter output

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

## Additional options

### Local wireless device access

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

### Display type

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

### Electronic cabling (for remote display)

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★
RQ	100 ft. (30.5 m) of cable (blue color)	★

### Bracket type, bracket material, and bolt material

Code	Description	
B4	Inline bracket, 304 Stainless steel (SST), 300 SST	★
BE	Inline bracket, 316 SST, 316 SST	★

### Tagging and fastener material

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

### RFID tagging

Code	Description	
Y3	RFID tag	★

### Transient protection

Code	Description	
T1	Transient terminal block	★

### Extended product warranty

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

### Pressure testing

Code	Description	
P1	Hydrostatic testing with certificate	

### Special cleaning

This is not available with graphite O-ring material, option code L2 or L3. Also, not available with graphite manifold valve packing.

Code	Description	
P2	Cleaning for special services	
P3	Cleaning for special services with testing for <1 ppm chlorine/fluorine	

### Software configuration

Code	Description	
C1	Custom software configuration (requires Configuration Data Sheet)	★

### Alarm limit

Code	Description	
C4	NAMUR alarm and saturation levels, high alarm	★
C5	NAMUR alarm and saturation levels, low alarm	★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm	★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm	★

Code	Description	
C8	Low alarm (standard Rosemount alarm and saturation levels)	★

(1) Options C6 and C7 require C1 and a Configuration Data Sheet.

## Swivel gauge adapter

This option is only available with process connection type A and process connection style 01, 02, or 03.

Code	Description	
SW	Swivel gauge adapter	★

## Ground screw

Code	Description	
X1	External ground screw assembly	★

## Sensor fill fluid

Code	Description	
L1	Inert sensor fill fluid	★

## Conduit plug

Code	Description	
DO	316 stainless steel (SST) conduit plug	★

## Conduit electrical connector

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

## Cold temperature

This is only available on pressure ranges 1–5, with silicone sensor fill fluid and stainless steel (SST) or Alloy C-276 isolating diaphragms and classic performance.

Code	Description	
BR5	-58 °F (-50 °C) cold temperature operation	★
BR6	-76 °F (-60 °C) cold temperature operation	★

## Process wetted thread sealant

Code	Description	
Z1	High temperature liquid thread sealant [-65 °F to 400 °F (-54 °C to 204 °C) temperature rating]	★

Code	Description	
Z2	Liquid thread sealant [-63 °F to 302 °F (-53 °C to 150 °C) temperature rating]	★
Z3	Anaerobic PTFE paste	★
Z4	GraFoil® thread sealant	★
Z5	Loctite® 580 thread sealant	★

### Custody transfer

Code	Description	
D3	Measurement Canada accuracy approval	★

### Drinking water approval

Code	Description	
DW	NSF drinking water approval	★

### Shipboard approvals

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

### Calibration certification

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

### Material traceability certification

Code	Description	
Q8	Material traceability certification per EN 10204 3.1	★

### Positive material identification (PMI)

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

### Quality certification for safety

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

## NACE® certificate

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

## Material recommendation for NACE®

This option is only available with process connection type A and process connection style 01, 02, or 03.

Code	Description	
SG	Sour gas (meets NACE MR0175/ISO 15156, MR0103/International Organization for Standardization (ISO) 17945)	★

## Product certifications

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

# Rosemount 4051SF Differential Pressure Flow Meters



4051SF Flow Meters integrate the 4051S with industry leading primary elements. Capabilities include:

- Emerson configures flow meters at the factory to meet your application needs (*DP Flow Configuration Data Sheet* required, available at [Emerson.com](https://www.emerson.com))
- 4–20 mA HART® protocol with two integral relay switches
- Ultra-For-Flow for improved flow performance across wider flow ranges
- Advanced diagnostics
- Direct or remote mount configurations available

## Online product configurator

Many products are configurable online using our product configurator.

Select the **Configure** button or visit [Emerson.com/global](https://www.emerson.com/global) to start. With this tool's built-in logic and continuous validation, you can configure your products more quickly and accurately.

## Specifications and options

The purchaser of the equipment must specify and select:

- Product materials
- Options
- Components

## Optimizing lead time

The starred offerings (★) represent the most common options and should be selected for the fastest delivery. The non-starred offerings are subject to additional delivery lead time.

## Sizing and selection

All Rosemount flow meters can be sized to meet your application specific requirements in the Differential pressure (DP) Flow sizing and selection tool. This tool will verify if a selected product meets your application requirements, provide a comparison between different primary elements, and generate a detailed accuracy comparison graph.

Once a sizing is completed, the configuration tool will help create a complete and valid model code to match your requirements and include any additional options or approvals.

## Rosemount 4051SFA Annubar™ Flow Meter



- Rosemount Annubar Flow Meters reduce permanent pressure loss by creating less blockage in the pipe.
- Ideal for large line size installations when cost, size, and weight of the flow meter are concerns.

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment.

[VIEW PRODUCT >](#)

[CONFIGURE >](#)

### Required model components

#### Model

Code	Description	
4051SFA	Annubar™ Flow Meter	★

#### Measurement functionality

Code	Description	
1	Flow (square root output)	★

#### Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

#### Performance class

Code	Description	
2 <sup>(1)</sup>	Ultra-For-Flow: 0.8% flow rate accuracy, 14:1 flow turndown, 20-year stability, 20-year limited warranty	★
4	Classic: 1.25% flow rate accuracy, 8:1 flow turndown, 20-year stability	★

(1) 28:1 flow turn down with universal pressure range option "U"

**Fluid type**

Code	Description	
L	Liquid	★
G	Gas	★
S	Steam	★

**Line size**

Code	Description	
020	2 in. (51 mm)	★
025	2½ in. (64 mm)	★
030	3 in. (80 mm)	★
035	3½ in. (89 mm)	★
040	4 in. (100 mm)	★
050	5 in. (125 mm)	★
060	6 in. (150 mm)	★
070	7 in. (175 mm)	★
080	8 in. (200 mm)	★
100	10 in. (250 mm)	★
120	12 in. (300 mm)	★
140	14 in. (350 mm)	★
160	16 in. (400 mm)	★
180	18 in. (450 mm)	★
200	20 in. (500 mm)	★
240	24 in. (600 mm)	★
300	30 in. (750 mm)	★
360	36 in. (900 mm)	★
420	42 in. (1,066 mm)	★
480	48 in. (1,210 mm)	★
600	60 in. (1,520 mm)	★
720	72 in. (1,820 mm)	★
780	78 in. (1,950 mm)	★
840	84 in. (2,100 mm)	★
900	90 in. (2,250 mm)	★
960	96 in. (2,400 mm)	★

**Pipe inside diameter (ID) range**

Code	Description	
Z	Custom manufactured for customer-supplied pipe ID	★

**Pipe material and mounting assembly material**

Code	Description	
C	Carbon steel (A105)	★
S	316 stainless steel (SST)	★
G	Chrome-Moly Grade F-11	★
N	Chrome-Moly Grade F-22	★
J	Chrome-Moly Grade F-91	★
0	No mounting (customer-supplied)	★

**Piping orientation**

Code	Description	
H	Horizontal piping	★
D	Vertical piping with downwards flow	★
U	Vertical piping with upwards flow	★

**Annubar™ type**

Code	Description	
P	Pak-Lok	★
F	Flanged with opposite side support	★
L	Flange-Lok	★
G	Gear-Drive Flo-Tap	★
M	Manual Flo-Tap	★

**Sensor material**

Code	Description	
S	316 stainless steel (SST)	★
H	Alloy C-276	★

**Sensor size**

Code	Description	
1	Sensor size 1 — Line sizes 2 in. (50 mm) to 8 in. (200 mm)	★
2	Sensor size 2 — Line sizes 6 in. (150 mm) to 96 in. (2,400 mm)	★
3	Sensor size 3 — Line sizes greater than 12 in. (300 mm)	★

**Mounting type**

Code	Description	
T1	Compression/threaded connection	★
A1	Class 150 RF American Society of Mechanical Engineers (ASME) B16.5	★
A3	Class 300 RF ASME B16.5	★

Code	Description	
A6	Class 600 RF ASME B16.5	★
A9	Class 900 RF ASME B16.5	★
AF	Class 1500 RF ASME B16.5	★
AT	Class 2500 RF ASME B16.5	★
D1	DN PN16 flange	★
D3	DN PN40 flange	★
D6	DN PN100 flange	★
R1	Class 150 ring type joint (RTJ) flange	★
R3	Class 300 RTJ flange	★
R6	Class 600 RTJ flange	★
R9	Class 900 RTJ flange	★
RF	Class 1500 RTJ flange	★
RT	Class 2500 RTJ flange	★

**Opposite side support and packing gland**

Code	Description		
0	No opposite side support or packing gland <sup>(1)</sup>		
<b>Opposite side support<sup>(2)</sup></b>			
C	NPT threaded opposite support assembly - extended tip		
D	Welded opposite support assembly - extended tip		
A	NPT threaded opposite support assembly - original (for retrofit)		
B	Welded opposite support assembly - original (for retrofit)		
<b>Packing gland<sup>(3)</sup></b>			
Code	Packing gland material	Rod material	Packing material
J	Stainless steel packing gland/cage nipple	Carbon steel	PTFE
K	Stainless steel packing gland/cage nipple	Stainless steel	PTFE
L	Stainless steel packing gland/cage nipple	Carbon steel	Graphite
N	Stainless steel packing gland/cage nipple	Stainless steel	Graphite
R	Alloy C-276 packing gland/cage nipple	Stainless steel	Graphite

(1) Required for Pak-Lok and Flange-Lok models.

(2) Required for flanged models.

(3) Required for Flo-Tap models.

**Isolation valve for Flo-tap models**

Code	Description	
1	Gate valve, carbon steel	★
2	Gate valve, stainless steel	★
3	Gate valve, Alloy C-276	★
5	Ball valve, carbon steel	★
6	Ball valve, stainless steel	★

Code	Description	
7	Ball valve, Alloy C-276	★
0	Not applicable or customer-supplied	★

### Transmitter connection platform

Code	Description	
3	Direct-mount, integral 3-valve manifold	★
5	Direct-mount, 5-valve manifold	★
6	Direct-mount, high temperature 5-valve manifold	★
7	Remote-mount NPT connections	★
8	Remote-mount SW connections	★

### Pressure measurement

Code	Description	
CD	Differential pressure, Coplanar™	★

### Pressure range

Code	Description	
U	Universal 28:1 flow turndown: 0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★
1	0 to 25 inH <sub>2</sub> O (0 to 0.0622 bar)	★
2	0 to 250 inH <sub>2</sub> O (0 to 0.6221 bar)	★
3	0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★

### Isolating diaphragm material

Code	Description	
2 <sup>(1)</sup>	316L stainless steel (SST)	★
3 <sup>(1)</sup>	Alloy C-276	★
4 <sup>(1)</sup>	Alloy 400	
5 <sup>(2)</sup>	Tantalum	
6 <sup>(1)(3)</sup>	Gold-plated Alloy 400	
7 <sup>(1)</sup>	Gold-plated 316L SST	

(1) *Materials of construction comply with metallurgical requirements highlighted within NACE® MR0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments. Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.*

(2) *Tantalum is not available with pressure range 1 and Q15.*

(3) *Includes a graphite-filled PTFE O-ring.*

### Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

**Transmitter housing material**

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

**Housing conduit/cable threads**

Code	Description	
1	½–14 NPT	★
2	M20 x 1.5	★
3 <sup>(1)</sup>	G½	★

(1) Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.

**Transmitter output**

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

**Additional options****Surface finish**

Code	Description	
RL	Surface finish for low pipe Reynolds number in gas and steam	★
RH	Surface finish for high pipe Reynolds number in liquid	★

**Installed in flanged pipe spool section**

Code	Description	
H3	Class 150 flanged connection with Rosemount standard length and schedule	
H4	Class 300 flanged connection with Rosemount standard length and schedule	
H5	Class 600 flanged connection with Rosemount standard length and schedule	

**Special shipment**

Code	Description	
Y1	Mounting hardware shipped separately	★

**Special dimensions**

Code	Description	
VM	Variable mounting	
VT	Variable tip	
VS	Variable length spool section	

**Manifold for remote mount option**

Code	Description	
F2	3-valve manifold, stainless steel	★
F3	3-valve manifold, Alloy C-276	★
F6	5-valve manifold, stainless steel	★
F7	5-valve manifold, Alloy C-276	★

**Instrument connections for remote mount option**

Code	Description	
G1	Needle valves, carbon steel	★
G2	Needle valves, stainless steel	★
G3	Needle valves, Alloy C-276	★
G5	Outside screw and yoke (OS&Y) gate valve, carbon steel	★
G6	OS&Y gate valve, stainless steel	★
G7	OS&Y gate valve, Alloy C-276	★

**Material testing**

Code	Description	
V1	Dye penetrant exam	

**Material examination**

Code	Description	
V2	Radiographic examination	

**Flow calibration**

Code	Description	
W1	Flow calibration (average K)	
W2	Special calibration	

**Special inspection**

Code	Description	
QC1	Visual and dimensional inspection with certificate	★
QC2	Inspection and performance certificate	★

**Code conformance**

Code	Description	
J2	American National Standards Institute (ANSI)/American Society of Mechanical Engineers (ASME) B31.1	
J3	ANSI/ASME B31.3	

### Country certification

Code	Description	
J1	Canadian Registration	★
J6	European Pressure Equipment Directive (PED)	★
J8	Chinese Certificate of Special Equipment Type Test	★

### Local wireless device access

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

### Display type

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

### Electronic cabling (for remote display)

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★
RQ	100 ft. (30.5 m) of cable (blue color)	★

### Transmitter time response

Code	Description	
P6 <sup>(1)</sup>	High-speed sensor time response	★

(1) Only available with differential pressure range 2 or 3 and diagnostics option A (**Loop Integrity** diagnostic will be disabled).

### Tagging and fastener material

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

### Custom tagging

Code	Description	
D6	Customer-specified barcode tag	★

**RFID tagging**

Code	Description	
Y3	RFID tag	★

**Transient protection**

Code	Description	
T1	Transient terminal block	★

**Extended product warranty**

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

**Pressure testing**

Code	Description	
P1	Hydrostatic testing with certificate	★
PX	Extended hydrostatic testing	★

**Special cleaning**

Code	Description	
P2	Cleaning for special services	

**Alarm limit**

Code	Description	
C4	NAMUR alarm and saturation levels, high alarm	★
C5	NAMUR alarm and saturation levels, low alarm	★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm	★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm	★
C8	Low alarm (standard Rosemount alarm and saturation levels)	★

<sup>(1)</sup> Options C6 and C7 require C1 and a Configuration Data Sheet.

**Ground screw**

Code	Description	
X1	External ground screw assembly	★

**Sensor fill fluid**

Code	Description	
L1	Inert sensor fill fluid	★

**O-ring**

Glass-filled PTFE O-ring is standard.

Code	Description	
L2	Graphite-filled PTFE O-ring	★
L3	All graphite gasket	★

**Conduit plug**

Code	Description	
DO	316 stainless steel (SST) conduit plug	★

**Conduit electrical connector**

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

**Cold temperature**

This is only available on pressure ranges 1–5, with silicone sensor fill fluid and stainless steel (SST) or Alloy C-276 isolating diaphragms and classic performance.

Code	Description	
BR5	-58 °F (-50 °C) cold temperature operation	★
BR6	-76 °F (-60 °C) cold temperature operation	★

**Shipboard approvals**

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

**Calibration certification**

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

**Material traceability certification**

Code	Description	
Q8	Material traceability certification per EN 10204 3.1	★

**Positive material identification (PMI)**

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

**Quality certification for safety**

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

**NACE® certificate**

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

**Product certifications**

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

## Rosemount 4051SFC Compact Flow Meter



- Compact conditioning flow meters reduce straight piping requirements to 2D upstream and 2D downstream from most flow disturbances.
- Simple installation of compact flow meters between any existing raised-face flanges.

[VIEW PRODUCT >](#)

[CONFIGURE >](#)

### Required model components

#### Model

Code	Description	
4051SFC	Compact Flow Meter	★

#### Measurement functionality

Code	Description	
1	Flow (square root output)	★

#### Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

#### Performance class

Code	Description	
2 <sup>(1)</sup>	Ultra-For-Flow: 0.75% flow rate accuracy, 14:1 flow turndown, 20-year stability, 20-year limited warranty	★
4	Classic: 1.1% flow rate accuracy, 8:1 flow turndown, 20-year stability	★

(1) 28:1 flow turn down with universal pressure range option "U"

#### Primary element technology

Code	Description	
C	Conditioning orifice plate	★
P	Orifice plate	★

**Material type**

Code	Description	
S	316 stainless steel (SST)	★

**Line size**

Code	Description	
005	½ in. (15 mm)	★
010	1 in. (25 mm)	★
015	1½ in. (40 mm)	★
020	2 in. (50 mm)	★
030	3 in. (80 mm)	★
040	4 in. (100 mm)	★
060	6 in. (150 mm)	★
080	8 in. (200 mm)	★
100	10 in. (250 mm)	★
120	12 in. (300 mm)	★

**Primary element style**

Code	Description	
N	Square edged	★

**Primary element type**

Code	Description	
040	0.40 Beta ratio	★
050	0.50 Beta ratio	★
065	0.65 Beta ratio	★

**Transmitter connection platform**

Code	Description	
3	Direct mount, integral 3-valve manifold	★
7	Remote mount, NPT connections	★

**Pressure measurement**

Code	Description	
CD	Differential pressure, Coplanar™	★

**Pressure range**

Code	Description	
U	Universal 28:1 flow turndown: 0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★

Code	Description	
1	0 to 25 inH <sub>2</sub> O (0 to 0.0622 bar)	★
2	0 to 250 inH <sub>2</sub> O (0 to 0.6221 bar)	★
3	0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★

### Isolating diaphragm material

Code	Description	
2 <sup>(1)</sup>	316L stainless steel (SST)	★
3 <sup>(1)</sup>	Alloy C-276	★
4 <sup>(1)</sup>	Alloy 400	
5 <sup>(2)</sup>	Tantalum	
6 <sup>(1)(3)</sup>	Gold-plated Alloy 400	
7 <sup>(1)</sup>	Gold-plated 316L SST	

(1) *Materials of construction comply with metallurgical requirements highlighted within NACE® MR0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments. Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.*

(2) *Tantalum is not available with pressure range 1 and Q15.*

(3) *Includes a graphite-filled PTFE O-ring.*

### Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

### Transmitter housing material

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

### Housing conduit/cable threads

Code	Description	
1	½–14 NPT	★
2	M20 x 1.5	★
3 <sup>(1)</sup>	G½	★

(1) *Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.*

### Transmitter output

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

## Additional options

### Installation accessories

Code	Description	
AB	American National Standards Institute (ANSI) alignment ring (Class 150) <sup>(1)</sup>	★
AC	ANSI alignment ring (Class 300) <sup>(1)</sup>	★
AD	ANSI alignment ring (Class 600) <sup>(1)</sup>	★
DG	DIN alignment ring (PN 16)	★
DH	DIN alignment ring (PN 40)	★
DJ	DIN alignment ring (PN 100)	★
JB	JIS alignment ring (10K)	★
JR	JIS alignment ring (20K)	★
JS	JIS alignment ring (40K)	★

(1) Only required for 10-in. (250 mm) and 12-in. (300 mm) line sizes.

### Remote adapters

Code	Description	
FE	Flange adapters 316 stainless steel (SST) (½-in. NPT)	★

### High temperature application

Code	Description	
HT	Graphite valve packing (T <sub>max</sub> = 850 °F [454 °C])	

### Manifold for remote mount option

Code	Description	
F2	3-valve manifold, stainless steel	★
F6	5-valve manifold, stainless steel	★

### Flow calibration

Code	Description	
WC	Flow calibration, 3-point, conditioning option C (all pipe schedules)	
WD	Flow calibration, 10-point, conditioning option C (all schedules)	

### Special inspection

Code	Description	
QC1	Visual and dimensional inspection with certificate	★
QC7	Inspection and performance certificate	★

**Code conformance**

Code	Description	
J2	American National Standards Institute (ANSI)/American Society of Mechanical Engineers (ASME) B31.1	
J3	ANSI/ASME B31.3	

**Country certification**

Code	Description	
J1	Canadian Registration	★
J8	Chinese Certificate of Special Equipment Type Test	★

**Local wireless device access**

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

**Display type**

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

**Electronic cabling (for remote display)**

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★
RQ	100 ft. (30.5 m) of cable (blue color)	★

**Transmitter time response**

Code	Description	
P6 <sup>(1)</sup>	High-speed sensor time response	★

(1) Only available with differential pressure range 2 or 3 and diagnostics option A (**Loop Integrity** diagnostic will be disabled).

**Tagging and fastener material**

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

**Custom tagging**

Code	Description	
D6	Customer-specified barcode tag	★

**RFID tagging**

Code	Description	
Y3	RFID tag	★

**Transient protection**

Code	Description	
T1	Transient terminal block	★

**Extended product warranty**

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

**Pressure testing**

Code	Description	
P1	Hydrostatic testing with certificate	

**Special cleaning**

Code	Description	
P2	Cleaning for special services	

**Alarm limit**

Code	Description	
C4	NAMUR alarm and saturation levels, high alarm	★
C5	NAMUR alarm and saturation levels, low alarm	★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm	★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm	★
C8	Low alarm (standard Rosemount alarm and saturation levels)	★

(1) Options C6 and C7 require C1 and a Configuration Data Sheet.

**Ground screw**

Code	Description	
X1	External ground screw assembly	★

**Sensor fill fluid**

Code	Description	
L1	Inert sensor fill fluid	★

**O-ring**

Code	Description	
L2	Graphite-filled PTFE O-ring	★

**Conduit plug**

Code	Description	
DO	316 stainless steel (SST) conduit plug	★

**Conduit electrical connector**

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

**Cold temperature**

This is only available on pressure ranges 1–5, with silicone sensor fill fluid and stainless steel (SST) or Alloy C-276 isolating diaphragms and classic performance.

Code	Description	
BR5	-58 °F (-50 °C) cold temperature operation	★
BR6	-76 °F (-60 °C) cold temperature operation	★

**Shipboard approvals**

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

**Calibration certification**

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

**Material traceability certification**

Code	Description	
Q8	Material traceability certification per EN 10204 3.1	★

**Positive material identification (PMI)**

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

**Quality certification for safety**

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

**NACE® certificate**

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

**Product certifications**

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

## Rosemount 4051SFP Integral Orifice Flow Meter



- Precision honed pipe section for increased accuracy in small line sizes.
- Self-centering plate design prevents alignment errors that magnify measurement inaccuracies in small line sizes.

The purchaser of the equipment must specify and select product materials, options, or components.

[VIEW PRODUCT >](#)
[CONFIGURE >](#)

### Required model components

#### Model

Code	Description	
4051SFP	Integral Orifice Flow Meter	★

#### Measurement functionality

Code	Description	
1	Flow (square root output)	★

#### Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

#### Performance class

Code	Description	
2 <sup>(1)</sup>	Ultra-For-Flow: 1.05% flow rate accuracy, 14:1 flow turndown, 20-year stability, 20-year limited warranty	★
4	Classic: 1.35% flow rate accuracy, 8:1 flow turndown, 20-year stability	★

(1) 28:1 flow turn down with universal pressure range option "U".

#### Body material and type

Code	Description	
F	316 stainless steel (SST), 4-bolt	★

**Line size**

Code	Description	
005	½ in. (15 mm)	★
010	1 in. (25 mm)	★
015	1½ in. (40 mm)	★

**Process connection (primary)**

Code	Description	
T1	NPT female body (not available with thermowell and RTD)	
S1	Socket weld body (not available with thermowell and RTD)	
P1	Pipe ends: NPT threaded	
P2	Pipe ends: beveled	
A1	Pipe ends: flanged, RF, American Society of Mechanical Engineers (ASME) B16.5 Class 150, slip-on	
A3	Pipe ends: flanged, RF, ASME B16.5 Class 300, slip-on	
A6	Pipe ends: flanged, RF, ASME B16.5 Class 600, slip-on	
D1	Pipe ends: flanged, RF, DIN PN16, slip-on	
D2	Pipe ends: flanged, RF, DIN PN40, slip-on	
D3	Pipe ends: flanged, RF, DIN PN100, slip-on	
W1	Pipe ends: flanged, RF, ASME B16.5 Class 150, weld-neck	
W3	Pipe ends: flanged, RF, ASME B16.5 Class 300, weld-neck	
W6	Pipe ends: flanged, RF, ASME B16.5 Class 600, weld-neck	
W9	Pipe ends: flanged, RF, ASME B16.5 Class 900, weld-neck	
R1	Pipe ends: flanged, ring type joint (RTJ) , ASME B16.5 Class 150, slip-on	
R3	Pipe ends: flanged, RTJ , ASME B16.5 Class 300, slip-on	
R6	Pipe ends: flanged, RTJ , ASME B16.5 Class 600, slip-on	
R9	Pipe ends: flanged, RTJ , ASME B16.5 Class 900, weld-neck	

**Orifice plate material**

Code	Description	
S	316/316L stainless steel (SST)	★
H	Alloy C-276	★
M	Alloy 400	★

**Bore size option**

Code	Description	
0010	0.01 in. (0.25 mm) for ½-in. pipe	★
0014	0.014 in. (0.36 mm) for ½-in. pipe	★
0020	0.02 in. (0.51 mm) for ½-in. pipe	★
0034	0.034 in. (0.86 mm) for ½-in. pipe	★

Code	Description	
0066	0.066 in. (1.68 mm) for ½-in. pipe	★
0109	0.109 in. (2.77 mm) for ½-in. pipe	★
0150	0.15 in. (3.81 mm) for 1-in. pipe	★
0160	0.16 in. (4.06 mm) for ½-in. pipe	★
0196	0.196 in. (4.98 mm) for ½-in. pipe	★
0250	0.25 in. (6.35 mm) for 1-in. pipe	★
0260	0.26 in. (6.6 mm) for ½-in. pipe	★
0295	0.295 in. (7.49 mm) for 1½-in. pipe	★
0340	0.34 in. (8.64 mm) for ½-in. pipe	★
0345	0.345 in. (8.76 mm) for 1-in. pipe	★
0376	0.376 in. (9.55 mm) for 1½-in. pipe	★
0500	0.5 in. (12.7 mm) for 1-in. pipe	★
0512	0.512 in. (13 mm) for 1½-in. pipe	★
0630	0.63 in. (16 mm) for 1-in. pipe	★
0748	0.748 in. (19 mm) for 1½-in. pipe	★
0800	0.8 in. (20.32 mm) for 1-in. pipe	★
1022	1.022 in. (25.96 mm) for 1½-in. pipe	★
1184	1.184 in. (30.07 mm) for 1½-in. pipe	★
XXXX	Special bore size (X.XXX in.)	★

### Transmitter connection platform

Code	Description	
D3	Direct mount, 3-valve manifold, stainless steel (SST)	★
D4	Direct-mount, 3-valve manifold, Alloy C-276	★
D5	Direct-mount, 5-valve manifold, SST	★
D6	Direct-mount, 5-valve manifold, Alloy C-276	★
R3	Remote-mount, 3-valve manifold, SST	★
R4	Remote-mount, 3-valve manifold, Alloy C-276	★
R5	Remote-mount, 5-valve manifold, SST	★
R6	Remote-mount, 5-valve manifold, Alloy C-276	★

### Pressure measurement

Code	Description	
CD	Differential pressure, Coplanar™	★

### Pressure range

Code	Description	
U	Universal 28:1 flow turndown: 0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★

Code	Description	
1	0 to 25 inH <sub>2</sub> O (0 to 0.0622 bar)	★
2	0 to 250 inH <sub>2</sub> O (0 to 0.6221 bar)	★
3	0 to 1,000 inH <sub>2</sub> O (0 to 2.49 bar)	★

### Isolating diaphragm material

Code	Description	
2 <sup>(1)</sup>	316L stainless steel (SST)	★
3 <sup>(1)</sup>	Alloy C-276	★
4 <sup>(1)</sup>	Alloy 400	
5 <sup>(2)</sup>	Tantalum	
6 <sup>(1)(3)</sup>	Gold-plated Alloy 400	
7 <sup>(1)</sup>	Gold-plated 316L SST	

(1) *Materials of construction comply with metallurgical requirements highlighted within NACE® MR0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments. Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.*

(2) *Tantalum is not available with pressure range 1 and Q15.*

(3) *Includes a graphite-filled PTFE O-ring.*

### Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

### Transmitter housing material

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

### Housing conduit/cable threads

Code	Description	
1	½–14 NPT	★
2	M20 x 1.5	★
3 <sup>(1)</sup>	G½	★

(1) *Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.*

### Transmitter output

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

## Additional options

### Transmitter/body bolt material

Code	Description
GT	Extended temperature gaskets, studs, and nuts (850 °F [454 °C])

### Optional connection

Code	Description
G1	DIN 19213 transmitter connection

### Material testing

Code	Description
V1	Dye penetrant exam

### Material examination

Code	Description
V2	Radiographic examination

### Flow calibration

Code	Description
WD	Discharge coefficient verification

### Special inspection

Code	Description
QC1	Visual and dimensional inspection with certificate
QC7	Inspection and performance certificate

### Code conformance

Code	Description
J2	American National Standards Institute (ANSI)/American Society of Mechanical Engineers (ASME) B31.1
J3	ANSI/ASME B31.3

### Country certification

Code	Description
J1	Canadian Registration
J6	European Pressure Equipment Directive (PED)

### Local wireless device access

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

### Display type

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

### Electronic cabling (for remote display)

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★
RQ	100 ft. (30.5 m) of cable (blue color)	★

### Transmitter time response

Code	Description	
P6 <sup>(1)</sup>	High-speed sensor time response	★

(1) Only available with differential pressure range 2 or 3 and diagnostics option A (**Loop Integrity** diagnostic will be disabled).

### Tagging and fastener material

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

### Custom tagging

Code	Description	
D6	Customer-specified barcode tag	★

### RFID tagging

Code	Description	
Y3	RFID tag	★

**Transient protection**

Code	Description	
T1	Transient terminal block	★

**Extended product warranty**

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

**Pressure testing**

Code	Description	
P1	Hydrostatic testing with certificate	

**Special cleaning**

Code	Description	
P2	Cleaning for special services	

**Alarm limit**

Code	Description	
C4	NAMUR alarm and saturation levels, high alarm	★
C5	NAMUR alarm and saturation levels, low alarm	★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm	★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm	★
C8	Low alarm (standard Rosemount alarm and saturation levels)	★

<sup>(1)</sup> Options C6 and C7 require C1 and a Configuration Data Sheet.

**Ground screw**

Code	Description	
X1	External ground screw assembly	★

**Sensor fill fluid**

Code	Description	
L1	Inert sensor fill fluid	★

**O-ring**

Glass-filled PTFE O-ring is standard.

Code	Description	
L2	Graphite-filled PTFE O-ring	★
L3	All graphite gasket	★

**Conduit plug**

Code	Description	
DO	316 stainless steel (SST) conduit plug	★

**Conduit electrical connector**

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

**Cold temperature**

This is only available on pressure ranges 1–5, with silicone sensor fill fluid and stainless steel (SST) or Alloy C-276 isolating diaphragms and classic performance.

Code	Description	
BR5	-58 °F (-50 °C) cold temperature operation	★
BR6	-76 °F (-60 °C) cold temperature operation	★

**Shipboard approvals**

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

**Calibration certification**

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

**Material traceability certification**

Code	Description	
Q8	Material traceability certification per EN 10204 3.1	★

**Positive material identification (PMI)**

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

**Quality certification for safety**

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

**NACE® certificate**

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

**Product certifications**

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

# Rosemount 4051SLT Level Transmitter



Rosemount 4051SLT Level Transmitters combine the features and benefits of a high-performance Rosemount 4051S with the durability and reliability of diaphragm seals all in a single model number.

Product features and capabilities include:

- Variety of process connections including flanged, threaded, and hygienic seals
- Quantified performance for the entire transmitter/seal assembly (QZ option)
- 4-20 mA HART® protocol with two integral relay switches

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment.

VIEW PRODUCT >
CONFIGURE >

## Specifications and options

The purchaser of the equipment must specify and select:

- Product materials
- Options
- Components

## Optimizing lead time

The starred offerings (★) represent the most common options and should be selected for the fastest delivery. The non-starred offerings are subject to additional delivery lead time.

## Ordering information

1. Specify all required model components. If process connection type option code B (remote seal) is selected, then specify a one seal system (01 or 02), two seal system (03, 04, 05, or 06), or an assemble-to system (07 or 08).
2. Refer to [Table 1](#) for details on the ordering process for seal types and process connection styles.

**Table 1: Ordering Process for Seal Types and Process Connection Styles**

Process connection type	Seal type	Process connection style	Order process
Option Code B (Remote Seal)	Flanged	Option codes 01, 02, 03, 04, 05 or 06 (one or two seal system)	Specify seal(s) in single model string
	Threaded		
	Hygienic	Option codes 07 or 08 (Assemble-to)	Additional seal model string(s) are required. Not applicable (-) option codes must be selected in 4051SLT model where listed, as those options will be specified in each individual seal model string.
	Saddle and Flow Through		

**Table 1: Ordering Process for Seal Types and Process Connection Styles (continued)**

Process connection type	Seal type	Process connection style	Order process
	Special		

- Note that if you are ordering a flanged or threaded seal, this must be specified and ordered through the 4051SLT model. These seal types cannot be ordered using an assemble-to option code and specifying a 1299 separately.

**Note**

If options 07 or 08 are selected, all “Not applicable” option codes are required in the following sections of the 4051SLT model, as they will be specified in the separate seal models:

- Fill fluid
- High side or inline connection
- Low side connection
- Industry standard
- Process connection size
- Flange pressure rating
- Flange material
- Seal diaphragm material
- Lower housing
- Flushing ring
- Seal extension length

See example below:

4051SLT system with flanged seal specified in one model:

- 4051SLT1A1CD22NB04NA1ADD00E10AH2SSNG0M6

4051SLT system with hygienic seals requiring separate models:

- 4051SLT1A1CD22NB08NA1A-----Q8M6
- 1199TDA93SSCW70LA00Q76
- 1199CDC10SSCW70LA00Q76

## Required model components

### Model

Code	Description	
4051SLT	Level Transmitter	★

### Measurement functionality

Code	Description	
1	Pressure, level, or flow (square root output) with remote seal	★

## Diagnostic functionality

Code	Description	
A	<b>Device</b> and <b>Loop Integrity</b> diagnostics	★
B	Enhanced SIS proof testing and logging (includes <b>Loop Integrity</b> diagnostic)	★
C	<b>Process Intelligence</b> with <b>Plugged Impulse Line</b> diagnostic (includes enhanced SIS and <b>Loop Integrity</b> )	★

## Performance class

Code	Description	
1	Ultra: 0.025% span accuracy, 200:1 rangedown, 20-year stability, 20-year limited warranty	★
4	Classic: 0.035% span accuracy, 150:1 rangedown, 20-year stability	★

## Pressure measurement and module type

Code	Description	
CD	Differential pressure, Coplanar	★
CG	Gauge pressure, Coplanar	★
TG	Gauge pressure, In-line	★
TA	Absolute pressure, In-line	★
CA	Absolute pressure, Coplanar	★

## Pressure range

Code	Description					
	Differential pressure Coplanar™	Gauge pressure Coplanar	Gauge pressure In-line	Absolute pressure In-line	Absolute pressure Coplanar	
1	-25 to 25 inH <sub>2</sub> O (-62.16 to 62.16 mbar)	-25 to 25 inH <sub>2</sub> O (-62.16 to 62.16 mbar)	-14.7 to 30 psig (-1.01 to 2.06 bar)	0 to 30 psia (0 to 2.06 bar)	0 to 30 psia (0 to 2.07 bar)	★
2	-250 to 250 inH <sub>2</sub> O (-621.60 to 621.60 mbar)	-250 to 250 inH <sub>2</sub> O (-621.60 to 621.60 mbar)	-14.7 to 150 psig (-1.01 to 10.34 bar)	0 to 150 psia (0 to 10.34 bar)	0 to 150 psia (0 to 10.34 bar)	★
3	-1,000 to 1,000 inH <sub>2</sub> O (-2.49 to 2.49 bar)	-393 to 1,000 inH <sub>2</sub> O (-0.97 to 2.49 bar)	-14.7 to 800 psig (-1.01 to 55.15 bar)	0 to 800 psia (0 to 55.15 bar)	0 to 800 psia (0 to 55.16 bar)	★
4	-300 to 300 psi (-20.68 to 20.68 bar)	-14.2 to 300 psig (-0.97 to 20.68 bar)	-14.7 to 4,000 psig (-1.01 to 275.79 bar)	0 to 4,000 psia (0 to 275.79 bar)	0 to 4,000 psia (0 to 275.79 bar)	★
5	-2,000 to 2,000 psi (-137.89 to 137.89 bar)	-14.2 to 2,000 psig (-0.97 to 137.89 bar)	-14.7 to 10,000 psig (-1.01 to 689.47 bar)	0 to 10,000 psia (0 to 689.47 bar)	N/A	★

## Transmitter isolating diaphragm material

Code	Description	
2	316L Stainless steel (SST)	★
3	Alloy C-276	★

## Process temperature measurement

Code	Description	
N	No process temperature measurement input	★

## Process connection type

Code	Description	
B	Remote seal	★
S	Remote seal — Thermal range expander (Silicone 200 secondary fill fluid)	★
U	Remote seal — Thermal range expander (SYLTHERM™ XLT secondary fill fluid)	★
V	Remote seal — Thermal range expander (Tri-Therm 300 secondary fill fluid)	★

## Process connection style

Code	Description	
<b>One seal system</b>		
01	One remote seal, welded-repairable	★
02	One remote seal, all-welded	★
<b>Two seal system</b>		
03	Tuned system, welded-repairable	★
04	Tuned system, all-welded	★
05	Balanced system, welded-repairable	★
06	Balanced system, all-welded	★
<b>Assemble-to</b>		
07	Assemble to one Rosemount remote seal (specified separately) <sup>(1)</sup>	★
08	Assemble to two Rosemount remote seals (specified separately) <sup>(2)</sup>	★

(1) *Have to build one other model which specifies high or low.*

(2) *Have to build two other models which specifies high or low.*

## Process connection material

Code	Description	
N	Material specified with diaphragm and flange remote seal options	★

## Transmitter housing material

Code	Description	
A	Aluminum	★
S	Stainless steel (SST)	★

## Housing conduit/cable threads

Code	Description	
1	½–14 NPT	★

Code	Description	
2	M20 x 1.5	★
3 <sup>(1)</sup>	G½	★

(1) Transmitter conduit entry will be ½ NPT, and a ½ NPT to G½ thread adapter will be provided.

## Transmitter output

Code	Description	
A	4–20 mA with digital signal based on HART® protocol	★
S	4–20 mA with digital signal based on HART protocol and two integral relay switches	★

## Fill fluid

Code	Fill fluid	Specific gravity at 77 °F (25 °C)	Temperature limits <sup>(1)(2)</sup>				
			No extension	2-in. (50 mm) extension	4-in. (100 mm) extension	Thermal optimizer	
- <sup>(3)</sup>	Not applicable	Not applicable	Not applicable				★
D	Silicone 200	0.934	–49 to 401 °F (–45 to 205 °C)				★
F	Silicone 200 for vacuum applications	0.934	For use in vacuum applications below 14.7 psia (1 bar-a). <sup>(4)</sup>				★
J <sup>(5)</sup>	Tri-Therm 300	0.795	–40 to 401 °F (–40 to 205 °C)	–40 to 464 °F (–40 to 240 °C)	–40 to 572 °F (–40 to 300 °C)	–40 to 572 °F (–40 to 300 °C)	★
Q <sup>(5)</sup>	Tri-Therm 300 for vacuum applications	0.795	For use in vacuum applications below 14.7 psia (1 bar-a). <sup>(4)</sup>				★
L	Silicone 704	1.07	32 to 401 °F (0 to 205 °C)	32 to 464 °F (0 to 240 °C)	32 to 572 °F (0 to 300 °C)	32 to 599 °F (0 to 315 °C)	★
C	Silicone 704 for vacuum applications	1.07	For use in vacuum applications below 14.7 psia (1 bar-a). <sup>(4)</sup>				★
R	Silicone 705	1.09	68 to 401 °F (20 to 205 °C)	68 to 464 °F (20 to 240 °C)	68 to 572 °F (20 to 300 °C)	68 to 698 °F (20 to 370 °C)	★
V	Silicone 705 for vacuum applications	1.09	For use in vacuum applications below 14.7 psia (1 bar-a). <sup>(4)</sup>				★
A <sup>(6)</sup>	SYLTHERM™ XLT	0.85	–157 to 293 °F (–105 to 145 °C)				★
H <sup>(6)</sup>	Inert (Halocarbon)	1.85	–49 to 320 °F (–45 to 160 °C)				★
G <sup>(5)(7)</sup>	Glycerine and water	1.13	5 to 203 °F (–15 to 95 °C)				★
N <sup>(5)(6)</sup>	Neobee® M-20	0.94	5 to 437 °F (–15 to 225 °C)	5 to 437 °F (–15 to 225 °C)			★

Code	Fill fluid	Specific gravity at 77 °F (25 °C)	Temperature limits <sup>(1)(2)</sup>				★
			No extension	2-in. (50 mm) extension	4-in. (100 mm) extension	Thermal optimizer	
p <sup>(5)(7)</sup>	Propylene Glycol and water	1.02	5 to 203 °F (-15 to 95 °C)				★

- (1) At ambient pressure of 14.7 psia (1 bar-a) and ambient temperature of 70 °F (21 °C).
- (2) Due to heat transfer to the transmitter, the maximum ambient temperature will be de-rated if the process temperature exceeds 185°F (85 °C). Consult application specialist.
- (3) Required with selection of process connection style option codes 07 or 08.
- (4) Refer to vapor pressure curves in [Rosemount DP Level Fill Fluid Specification Technical Note](#).
- (5) This is a food grade fill fluid.
- (6) For use in vacuum applications below 14.7 psia (1 bar-a), refer to vapor pressure curves in [Rosemount DP Level Fill Fluid Specification Technical Note](#).
- (7) Not suitable for vacuum applications.

### High side or inline connection

Code	Description	★
...(1)	Not applicable	★
000	No seal connection	★
<b>Direct mount connections</b>		
D00	Direct mount, no extension	★
D02	Direct mount, 2-in. (50 mm) extension	★
D04	Direct mount, 4-in. (100 mm) extension	★
D05 <sup>(2)</sup>	Direct mount, thermal optimizer	★
<b>Capillary lengths<sup>(3)</sup></b>		
Exx	1- to 50-ft., 5-ft. increments Example: 5-ft. = E05, 50-ft. = E50	★
Mxx	0.5- to 4-m, 0.5-m increments; 4- to 30-m with 1-m increments Example: 1-m = M01, 15-m = M15; exception: 0.5 = M50, 1.5-m = M51, 2.5-m = M52, 3.5-m = M53	

- (1) Required with selection of process connection style option codes 07 or 08.
- (2) Only available with In-line sensor type (Pressure measurement and module type option code TG or TA).
- (3) Capillary lengths below 25 feet (8 meters) are common options and should be selected for best delivery.

### Low side connection

Code	Description	★
...(1)	Not applicable	★
000	No seal connection	★
<b>Direct mount connections</b>		
D00	Direct mount, no extension	★
D02	Direct mount, 2-in. (50 mm) extension	★
D04	Direct mount, 4-in. (100 mm) extension	★
<b>Capillary lengths<sup>(2)</sup></b>		
Exx	1- to 50-ft., 5-ft. increments Example: 5-ft. = E05, 50-ft. = E50	

Code	Description
Mxx	0.5- to 4-m, 0.5-m increments; 4- to 30-m with 1-m increments Example: 1-m = M01, 15-m = M15; exception: 0.5 = M50, 1.5-m = M51, 2.5-m = M52, 3.5-m = M53

- (1) Required with selection of process connection style option codes 07 or 08.  
(2) Capillary lengths below 25 feet (8 meters) are common options and should be selected for best delivery.

## Industry standard

Code	Description	
-(1)	Not applicable	★
A	ASME B16.5/ASME B1.20.1	★
D	EN 1092-1/EN 10226-1/ISO 228-1	★
G	HG20615 (China Standard based on ASME B16.5)	★
K	HG20592 (China Standard based on EN 1092-1)	★
T	GOST 33259-15	★
B	ISA Threaded, B1.20.1 per ISA 82.03	★
J	JIS B2220 (Japanese Industrial Standard)	★

- (1) Required with selection of Process connection style option codes 07 or 08.

## Process connection size

Code	Description					
	Seal type	Industry Standard Code: A: ASME B16.5   ASME B1.20.1 G: HG20615 (China Standard based on ASME B16.5)	Industry Standard Code: D: EN 1092-1   EN 10226-1/ISO 228-1 K: HG20592 (China Standard based on EN 1092-1) T: GOST 33259-15	Industry Standard Code: J: JIS B2220 (Japanese Industrial Standard)	Industry Standard Code: B: ISA Threaded, B1.20.1 per ISA 82.03	
-(1)	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	★
A	Offline flanged	½ in.	N/A	N/A	N/A	★
B	Offline flanged	¾ in.	DN 10	10A	N/A	★
C	Offline flanged	N/A	DN 15	15A	N/A	★
D	Offline flanged	N/A	DN 20	20A	N/A	★
E	Offline flanged	1 in.	DN 25	25A	N/A	★
F	Offline flanged/ flush flanged/ Extended flanged	1½ in.	DN 40	40A	N/A	★
G	Flush flanged/ Pancake	2 in.	DN 50	50A	N/A	★
H	Flush flanged/ Pancake	3 in.	DN 80	80A	N/A	★
J	Flush flanged	4 in.	DN 100	100A	N/A	★

Code	Description					
	Seal type	Industry Standard Code: A: ASME B16.5   ASME B1.20.1 G: HG20615 (China Standard based on ASME B16.5)	Industry Standard Code: D: EN 1092-1   EN 10226-1/ISO 228-1 K: HG20592 (China Standard based on EN 1092-1) T: GOST 33259-15	Industry Standard Code: J: JIS B2220 (Japanese Industrial Standard)	Industry Standard Code: B: ISA Threaded, B1.20.1 per ISA 82.03	
K	Offline threaded	¼-18 FNPT	Tapered R½ per ISO 7/1 female threaded	N/A	N/A	★
L	Offline threaded	⅜-18 FNPT	G½ (EN 837-1) female threaded	N/A	¼-18 FNPT	★
M	Offline threaded	½-14 FNPT	N/A	N/A	⅜-18 FNPT	★
N	Offline threaded	¾-14 FNPT	N/A	N/A	½-14 FNPT	★
P	Offline threaded	1-11.5 FNPT	N/A	N/A	¾-14 FNPT	★
Q	Offline threaded	1¼-11.5 FNPT	N/A	N/A	1-11.5 FNPT	★
R	Offline threaded	1½-11.5 FNPT	N/A	N/A	1¼-11.5 FNPT	★

(1) Required with selection of process connection style option codes 07 or 08.

### Flange/pressure rating

Code	Description					
	Industry Standard Code: A: ASME B16.5   ASME B1.20.1 G: HG20615 (China Standard based on ASME B16.5)		Industry Standard Code: D: EN 1092-1   EN 10226-1/ISO 228-1 K: HG20592 (China Standard based on EN 1092-1) T: GOST 33259-15	Industry Standard Code: J: JIS B2220 (Japanese Industrial Standard)	Industry Standard Code: B: ISA Threaded, B1.20.1 per ISA 82.03	
	Process connection size code: A, B, E, F, G, H, and J	Process connection size code: K, L, M, N, P, Q, R, S, T, and U				
-(1)	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	★
0	No flange	N/A	No flange	N/A	N/A	★
1	Class 150	800 psi (55.2 bar)	PN 6	10K	1,700 psi (117.2 bar)	★
2	Class 300	2,500 psi (34.5 bar)	PN 10/16	20K	6,800 psi (468.8 bar)	★
3	Class 600	5,000 psi (344.7 bar)	PN 40	40K	10,200 psi (703.3 bar)	★
4	Class 900	10,000 psi (689.5 bar)	PN 63	N/A	13,700 psi (944.6 bar)	★
5	Class 1500	8,700 psi (599.8 bar)	PN 100	N/A	N/A	★

Code	Description					
	Industry Standard Code: A: ASME B16.5   ASME B1.20.1 G: HG20615 (China Standard based on ASME B16.5)		Industry Standard Code: D: EN 1092-1   EN 10226-1/ISO 228-1 K: HG20592 (China Standard based on EN 1092-1) T: GOST 33259-15	Industry Standard Code: J: JIS B2220 (Japanese Industrial Standard)	Industry Standard Code: B: ISA Threaded, B1.20.1 per ISA 82.03	
	Process connection size code: A, B, E, F, G, H, and J	Process connection size code: K, L, M, N, P, Q, R, S, T, and U				
6	Class 2500	1,500 psi (103.4 bar)	PN 160	N/A	N/A	★

(1) Required with selection of process connection style option codes 07 or 08.

## Flange material

Code	Description	
-(1)	Not applicable	★
N	No flange	★
C <sup>(2)</sup>	Carbon steel	★
S	316 Stainless steel (SST)	★

(1) Required with selection of process connection style option codes 07 or 08.

(2) Not available with one-piece design (alternate design option code M2).

## Seal diaphragm material

Code	Description	
-(1)	Not applicable	★
S <sup>(3)</sup>	316L stainless steel (SST)	★
H	Alloy C-276	★
T	Tantalum	★
D	Duplex 2205 SST	★
M	Alloy 400	★
B <sup>(2)(3)(4)</sup>	Tantalum (brazed)	★
A	304L SST	★
E	321 SST	★
F	Alloy B	★
G	Alloy C-22	★
J	Alloy 20	★
K	Alloy 600	★
L	Alloy 625	★
V	Duplex 2507 SST	★
W	Nickel 201	★
P	Titanium Grade 2	★
Q <sup>(5)</sup>	Titanium Grade 4	★

Code	Description	
R <sup>(5)</sup>	Zirconium 702	★

- (1) Required with selection of process connection style option codes 07 or 08.
- (2) Not available with one-piece design (alternate design option code M2).
- (3) For use with spiral wound metallic gaskets.
- (4) Only available for process connections G and H.
- (5) Operating temperature limited to 302 °F (150 °C).

### Lower housing, flushing ring, and seal extension length

Code	Description	
-(1)	Not applicable	★
N	No lower housing, flushing ring, or seal extension length	★
<b>Lower housing/flushing ring materials</b>		
P	Plated carbon steel	★
S	316L Stainless steel (SST)	★
H	Alloy C-276	★
T	Tantalum lined 316L SST	★
A	304L SST	★
D	Duplex 2205 SST	★
M	Alloy 400	★
Q	Titanium grade 4	★
<b>Assemble-to</b>		
Y	Assemble to 319 lower with valves, 319 specified separately	★
<b>Seal length extensions<sup>(2)</sup></b>		
0	0-in. (0 mm) Extension length	★
1	1-in. (25 mm) Extension length	★
2	2-in. (50 mm) Extension length	★
3	3-in. (75 mm) Extension length	★
4	4-in. (100 mm) Extension length	★
5	5-in. (125 mm) Extension length	★
6	6-in. (150 mm) Extension length	★
7	7-in. (175 mm) Extension length	★
8	8-in. (200 mm) Extension length	★
9	9-in. (225 mm) Extension length	★

- (1) Required with selection of process connection style option codes 07 or 08.
- (2) Extension length options are valid with extended flanged seals only.

### Other seal specific options

#### Intermediate gasket material

Code	Description	
G0	None — user-supplied intermediate gasket	★

Code	Description	
G2	C-4401	★
G3	KLINGER® Top-Chem 2000 PTFE	★
G4	Barium Sulfate-filled PTFE	★
G5	GraFoil®	★
G6	Ethylene Propylene	★

### Flushing connection

Code	Description	
F0	No flushing connection	★
F1	One (¼-18 NPT)	★
F2	Two (¼-18 NPT)	★
F4	One (½-14 NPT)	★
F5	Two (½-14 NPT)	★

### Flushing plugs/vents

Code	Description	
FB	316 Stainless steel (SST) plugs	★
FC	316 SST drain/vent valves	★
FD	Alloy C-276 plugs	★

### Flushing ring alignment clamp

#### Note

Available with process connection size option codes G, H, and J.

Code	Description	
FA	Flushing ring alignment clamp	★

### Extension diameter

Extension diameter options are valid with Extended Flanged Seals only.

Code	Description			
	English	Metric	Process connection size	
E145	1.45 in.	37 mm	1½ in.	★
E190	1.90 in.	48 mm	2 in.	★
E258	2.58 in.	66 mm	3 in. schedule 80	★
E285	2.85 in.	72 mm	3 in. schedule 40	★
E287	2.87 in.	73 mm	3 in. headbox	★
E299	2.99 in.	76 mm	3 in.	★
E350	3.50 in.	89 mm	4 in. schedule 80	★
E370	3.70 in.	94 mm	4 in. schedule to 40	★

Code	Description			
	English	Metric	Process connection size	
E378	3.78 in.	96 mm	4 in. headbox	★

### Extension and gasket surface material

Extension and gasket surface material options are valid with Extended Flanged Seals only.

Code	Description	
E0	Same as diaphragm material	★
E8	316L Stainless steel (SST)	★
E9	Alloy C-276	★

### Fractional extension length — English/Metric

Fractional extension length options are valid with Extended Flanged Seals only.

Code	Description	
A1	1/8-in. Additional extension	★
A2	1/4-in. Additional extension	★
A3	3/8-in. (5 mm) Additional extension	★
A4	1/2-in. (10 mm) Additional extension	★
A5	5/8-in. (15 mm) Additional extension	★
A6	3/4-in. (20 mm) Additional extension	★
A7	7/8-in. Additional extension	★

### Alternate capillary inner dimension (ID)

Standard capillary ID is 0.04-in. (1.092 mm) ID.

Code	Description	
T2	0.03-in. (0.711 mm) ID	★
T3	0.075-in. (1.905 mm) ID	★

### Capillary construction

Default capillary construction is 316L Stainless steel (SST) tube and 304 SST capillary armor.

Code	Description	
T4	PVC coated capillary, with closed end	★
T8	4-in. (101.6 mm) Support tube, PVC coated capillary, with closed end	★
T9	4-in. (101.6 mm) Support tube	★

### Radial capillary connection

Code	Description	
P5	Radial capillary connection	★

**Material traceability**

Code	Description	
Q8	Material traceability certification per EN 10204:2004 3.1B	★

**NACE® certificate**

Materials of construction comply with metallurgical requirements highlighted within NACE MR 0175/International Organization for Standardization (ISO) 15156 for sour oil field production environments.

Environmental limits apply to certain materials. Consult latest standard for details. Selected materials also conform to NACE MR 0103 for sour refining environments. Order with Q15 or Q25 to receive a NACE certificate.

Code	Description	
Q15	Certificate of compliance to NACE MR0175/ISO 15156 for wetted materials	★
Q25	Certificate of compliance to NACE MR0103/ISO 17945 for wetted materials	★

**Positive material identification (PMI)**

PMI verification and certificate requires Q8.

Code	Description	
Q76	PMI verification and certificate	★

**Diaphragm coating**

Code	Description	
H1	PTFE coated diaphragm for nonstick purposes only	★
H2	0.0002-in. (5 µm) gold-plated diaphragm	★
H5	Corrosion Shield PFA coated diaphragm	★

**Diaphragm thickness**

Code	Description	
DA	0.002 in. (50 µm) Diaphragm thickness	★
DB	0.006 in. (150 µm) Diaphragm thickness	★

**Remote seal bolt material**

Code	Description	
S2	316 stainless steel (SST) bolts	★
S3	316 SST bolts - studs not included	★
S4	304 SST bolts	★

**Alternate design**

Spiral wound gasket not available with all diaphragm materials. Consult [DP Level Sizing and Selection Tool](#).

Code	Description	
M1	Solid faceplate (same as diaphragm material)	★

Code	Description	
M2	One-piece design	★

### Modified flanged connection

Code	Description	
V1	Ring Type Joint flanged connection	★

### Extended product warranty

Code	Description	
WR3	3-year limited warranty	★
WR5	5-year limited warranty	★

### Seal system performance reports

Process conditions required to run report. Consider using a [Configuration Data Sheet](#).

Code	Description	
QZ	Remote seal system performance calculation report	★

## Additional options

### Local wireless device access

Code	Description	
BLE	Bluetooth® configuration and maintenance	★

### Display type

Code	Description	
M6	Graphical backlit LCD display with <b>Quick Service</b> buttons	★
M8 <sup>(1)</sup>	Remote graphical backlit LCD display and interface, <b>Quick Service</b> buttons	★

(1) An electronic cable must be specified if ordering a remote display.

### Electronic cabling (for remote display)

Additional cable lengths are available up to 500 ft. (152.4 m). Consult the product configurator on [Emerson.com/global](https://www.emerson.com/global) or your local Emerson sales representative for more information.

Code	Description	
RA	25 ft. (7.62 m) of cable (gray color)	★
RB	50 ft. (15.2 m) of cable (gray color)	★
RC	100 ft. (30.5 m) of cable (gray color)	★
RN	25 ft. (7.62 m) of cable (blue color)	★
RP	50 ft. (15.2 m) of cable (blue color)	★

Code	Description	
RQ	100 ft. (30.5 m) of cable (blue color)	★

### Bracket type, bracket material, and bolt material

Code	Description	
B4	Coplanar™ flange bracket for 2-in. pipe and panel, 304 stainless steel (SST), 300 SST	★
BE	Coplanar flange bracket for 2-in. pipe and panel, 316 SST, 316 SST	★

### Tagging and fastener material

Code	Description	
Y2	316 stainless steel (SST) nameplate, top tag, wire-on tag, and fasteners	★

### RFID tagging

Code	Description	
Y3	RFID tag	★

### Bolting material

Code	Description	
L4	Austenitic 316 stainless steel (SST) bolts	★
L5	ASTM A193, Grade B7M bolts	★
L6	Alloy K-500 bolts	★
L7 <sup>(1)</sup>	ASTM A453, Class D, Grade 660 bolts	★
L8	ASTM A193, Class 2, Grade B8M bolts	★

(1) Bolts are not considered process-wetted. In instances where NACE® MR0175/International Organization for Standardization (ISO) 15156 and NACE MR0103 conformance is required for bolting, L7 is the recommended bolting option.

### Transient protection

Code	Description	
T1	Transient terminal block	★

### Pressure testing

Code	Description	
P1	Hydrostatic testing with certificate	

### Special cleaning

This is not available with graphite O-ring material, option code L2 or L3. Also, not available with graphite manifold valve packing.

Code	Description	
P2	Cleaning for special services	

Code	Description
P3	Cleaning for special services with testing for <1 ppm chlorine/fluorine

### Software configuration

Code	Description
C1	Custom software configuration (requires Configuration Data Sheet) ★

### Alarm limit

Code	Description
C4	NAMUR alarm and saturation levels, high alarm ★
C5	NAMUR alarm and saturation levels, low alarm ★
C6 <sup>(1)</sup>	Custom alarm and saturation signal levels, high alarm ★
C7 <sup>(1)</sup>	Custom alarm and saturation signal levels, low alarm ★
C8	Low alarm (standard Rosemount alarm and saturation levels) ★

(1) Options C6 and C7 require C1 and a Configuration Data Sheet.

### Flange adapter

The flange adapter material will match the material selected in the process connection size.

Code	Description
D2	Flange adapter(s) ★

### Ground screw

Code	Description
X1	External ground screw assembly ★

### Drain/vent valve

Code	Description
D5	Remove transmitter drain/vent valves (install plugs) ★
D8	Ceramic drain/vent valves ★
FJ	Low side drain/vent (Coplanar™ transmitter with one remote seal)

### Sensor fill fluid

Code	Description
L1	Inert sensor fill fluid ★

## O-ring

Glass-filled PTFE O-ring is standard.

Code	Description	
L2	Graphite-filled PTFE O-ring	★
L3	All graphite gasket	★

## Conduit plug

Code	Description	
DO	316 stainless steel (SST) conduit plug	★

## Conduit electrical connector

This is not available with explosion-proof or flameproof approvals.

Code	Description	
GE	M12, 4-pin, male connector (eurofast®)	★
GM	A size mini, 4-pin, male connector (minifast®)	★
GB	M20 ATEX-certified cable gland and plug	★

## Process wetted thread sealant

Code	Description	
Z1	High temperature liquid thread sealant [-65 °F to 400 °F (-54 °C to 204 °C) temperature rating]	★
Z2	Liquid thread sealant [-63 °F to 302 °F (-53 °C to 150 °C) temperature rating]	★
Z3	Anaerobic PTFE paste	★
Z4	GraFoil® thread sealant	★
Z5	Loctite® 580 thread sealant	★

## Shipboard approvals

Code	Description	
SBS	American Bureau of Shipping	★
SBV	Bureau Veritas (BV) Type Approval	★
SDN	Det Norske Veritas (DNV) Type Approval	★
SLL	Lloyd's Register (LR) Type Approval	★

## Calibration certification

Code	Description	
Q4	Calibration certificate	★
QP	Calibration certificate and tamper evident seal	★

### Quality certification for safety

Code	Description	
QT	Safety-certified to IEC 61508 with certificate of Failure Modes, Effects, and Diagnostic Analysis (FMEDA) data	★

### Product certifications

Code	Description	
K1	ATEX Flameproof, Intrinsic Safety, Zone 2 Increased Safety, Dust	★
E1	ATEX Flameproof, Dust	★
I1	ATEX Intrinsic Safety	★
N1	ATEX Zone 2 Increased Safety	★
K5	USA Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E5	USA Explosion-proof, Dust, Non-Incendive	★
I5	USA Intrinsic Safety, Non-incendive	★
K6	Canada Explosion-proof, Dust, Intrinsic Safety, Non-Incendive	★
E6	Canada Explosion-proof, Dust, Non-Incendive	★
I6	Canada Intrinsic Safety, Non-incendive	★
K7	IECEX Flameproof, Dust, Intrinsic Safety, Zone 2 Increased Safety	★
E7	IECEX Flameproof, Dust	★
I7	IECEX Intrinsic Safety	★
N7	IECEX Zone 2 Increased Safety	★
KS	USA, Canada, IECEX and ATEX Flameproof, Intrinsic Safety, Dust, Zone 2 Increased Safety, Non-Incendive	★
KL	USA, Canada, IECEX, ATEX Intrinsic Safety	★

# Specifications

## Performance specifications

### Conformance to specification

Technology leadership, advanced manufacturing techniques, and statistical process control ensure pressure measurement specification conformance to  $\pm 3\sigma$  or better.

### Reference accuracy

Stated reference accuracy equations include terminal based linearity, hysteresis, repeatability, and setability.

**Table 2: Transmitter with Coplanar™ Sensor Module**

<b>Differential pressure (4051S_CD)</b>			
<b>Gauge pressure (4051S_CG)</b>			
<b>Range</b>	<b>Ultra</b>	<b>Classic</b>	<b>Ultra-For-Flow<sup>(1)</sup></b>
Range 0	$\pm 0.09\%$ of span; For spans less than 2:1, $\pm 0.045\%$ of upper range limit (URL)	$\pm 0.10\%$ of span; For spans less than 2:1, $\pm 0.05\%$ of URL	N/A
Range 1	$\pm 0.09\%$ of span; For spans less than 15:1, $\pm(0.015 + 0.005[\text{URL}/\text{Span}])\%$ of span	$\pm 0.10\%$ of span; For spans less than 15:1, $\pm(0.025 + 0.005[\text{URL}/\text{Span}])\%$ of span	N/A
Ranges 2–4	$\pm 0.025\%$ of span; For spans less than 10:1, $\pm(0.005 + 0.0035[\text{URL}/\text{Span}])\%$ of span	$\pm 0.035\%$ of span; For spans less than 10:1, $\pm(0.015 + 0.005[\text{URL}/\text{Span}])\%$ of span	$\pm 0.04\%$ of reading up to 8:1 differential pressure (DP) turndown from URL; $\pm(0.04 + 0.0023[\text{URL}/\text{Reading}])\%$ of reading to 200:1 DP turndown from URL
Range 5	$\pm 0.05\%$ of span; For spans less than 10:1, $\pm(0.005 + 0.0045[\text{URL}/\text{Span}])\%$ of span	$\pm 0.065\%$ of span; For spans less than 10:1, $\pm(0.015 + 0.005[\text{URL}/\text{Span}])\%$ of span	N/A
Range U	$\pm 0.025\%$ of span; For spans from 10:1 and 200:1, $\pm(0.005 + 0.0035[\text{URL}/\text{Span}])\%$ of span For spans less than 200:1, $\pm(0.615 + 0.0005[\text{URL}/\text{Span}])\%$ of span	N/A	$\pm 0.04\%$ Reading up to 8:1 DP Turndown from URL; $\pm (0.04 + 0.0023 [\text{URL}/\text{Reading}])\%$ of reading to 200:1 DP turndown from URL $\pm (0.32 + 0.0008\% [\text{URL}/\text{Reading}])\%$ of reading for >200:1 to 800:1 DP turndown from URL
<b>Absolute pressure (4051S_CA)</b>			
<b>Range</b>	<b>Ultra</b>	<b>Classic</b>	
Ranges 0	$\pm 0.075\%$ of span; For spans less than 5:1, $\pm(0.025 + 0.01[\text{URL}/\text{Span}])\%$ of span	$\pm 0.075\%$ of span; For spans less than 5:1, $\pm(0.025 + 0.01[\text{URL}/\text{Span}])\%$ of span	
Ranges 1–4	$\pm 0.025\%$ of span; For spans less than 10:1, $\pm(0.004[\text{URL}/\text{Span}])\%$ of span	$\pm 0.035\%$ of span; For spans less than 10:1, $\pm(0.0065[\text{URL}/\text{Span}])\%$ of span	

(1) Ultra-For-Flow is only applicable for Rosemount 4051S\_CD ranges 2–3 only. For calibrated spans from 1:1 to 2:1 of URL, add  $\pm 0.005\%$  of span analog output error.

**Table 3: Transmitter with In-Line Sensor Module**

Absolute pressure (4051S_TA) Gauge pressure (4051S_TG)		
Range	Ultra	Classic
Ranges 1-4	±0.025% of span For spans less than 10:1, ±(0.004[URL/Span])% of span	±0.035% of span For spans less than 10:1, ±(0.0065[URL/Span])% of span
Ranges 5	±0.04% of span; For spans less than 10:1 ±0.004% of URL	±0.065% of span; For spans less than 10:1 ±0.0065% of URL

**Table 4: Level Transmitter**

Gauge pressure (4051SLT_CG), (4051SLT_TG) Absolute pressure (4051SLT_CA), (4051SLT_TA) Differential pressure (4051SLT_CD)		
Range	Ultra	Classic
Ranges 1-5	±0.055% of span For spans less than 10:1, ±(0.015 + 0.005[URL/Span])% of span	±0.065% of span For spans less than 10:1, ±(0.015 + 0.005[URL/Span])% of span

**Transmitter total performance**

Total performance is based on combined errors of reference accuracy, ambient temperature effects, and line pressure effects at normal operating conditions (70 percent of span typical reading, 740 psi [51 bar] line pressure). For performance of ranges not listed, please contact the factory.

Models	Range	Ultra	Classic	Ultra-For-Flow
4051S_CD	Ranges 2-3	±0.1% of span For ±50 °F (+/-28 °C) temperature changes; 0-100% relative humidity, from 1:1 to 5:1 rangedown	±0.14% of span For ±50 °F (+/-28 °C) temperature changes, 0-100% relative humidity, from 1:1 to 5:1 rangedown	±0.15% of reading For ±50 °F (28 °C) temperature changes, 0-100% relative humidity, over 8:1 DP turndown from URL
4051S_CG	Ranges 2-5			
4051S_T	Ranges 2-4			
4051S_CA	Ranges 2-4			

**Flow performance**

**NOTICE**

These flow measurement accuracies assume a constant density, viscosity, and expansibility factor.

**NOTICE**

Range 1 flow meters experience an additional uncertainty up to 0.9%. Consult your Emerson representative for exact specifications.

**NOTICE**

Consult the [DP Flow Sizing and Selection Tool](#) for performance specifications related to universal range flow meters.

**Table 5: Flow Meter Performance Specifications**

Flow performance specifications assume the device only uses differential pressure (DP) readings without pressure and temperature compensation.

Models	Ultra	Classic	Ultra-For-Flow
<b>Annubar™ flow meter Rosemount 4051SFA</b>			
Ranges 2-3	±0.95% of flow rate at 8:1 flow turndown	±1.25% of flow rate at 8:1 flow turndown	±0.80% of flow rate at 14:1 flow turndown

**Table 5: Flow Meter Performance Specifications (continued)**

Compact conditioning orifice flow meter 4051SFC_C			
Ranges 2-3			
$\beta = 0.4$	$\pm 0.90\%$ of flow rate at 8:1 flow turndown	$\pm 1.10\%$ of flow rate at 8:1 flow turndown	$\pm 0.75\%$ of flow rate at 14:1 flow turndown
$\beta = 0.50, 0.65$	$\pm 1.25\%$ of flow rate at 8:1 flow turndown	$\pm 1.40\%$ of flow rate at 8:1 flow turndown	$\pm 1.15\%$ of flow rate at 14:1 flow turndown
Compact orifice flow meter 4051SFC_P <sup>(1)</sup>			
Ranges 2-3	$\pm 1.35\%$ of flow rate at 8:1 flow turndown	$\pm 1.80\%$ of flow rate at 8:1 flow turndown	$\pm 1.30\%$ of flow rate at 14:1 flow turndown
Integral orifice flow meter (4051SFP)			
Ranges 2-3			
Bore < 0.160	$\pm 2.65\%$ of flow rate at 8:1 flow turndown	$\pm 2.70\%$ of flow rate at 8:1 flow turndown	$\pm 2.60\%$ of flow rate at 14:1 flow turndown
$0.160 \leq \text{Bore} < 0.500$	$\pm 1.70\%$ of flow rate at 8:1 flow turndown	$\pm 1.80\%$ of flow rate at 8:1 flow turndown	$\pm 1.60\%$ of flow rate at 14:1 flow turndown
$0.500 \leq \text{Bore} \leq 1.000$	$\pm 1.25\%$ of flow rate at 8:1 flow turndown	$\pm 1.35\%$ of flow rate at 8:1 flow turndown	$\pm 1.15\%$ of flow rate at 14:1 flow turndown
$1.000 < \text{Bore}$	$\pm 1.70\%$ of flow rate at 8:1 flow turndown	$\pm 1.80\%$ of flow rate at 8:1 flow turndown	$\pm 1.60\%$ of flow rate at 14:1 flow turndown

(1) For line sizes less than 2 in. (50 mm) or greater than 8 in. (200 mm), add an additional 5 percent uncertainty.

## Long term stability

Models	Range	Ultra	Classic	Ultra-For-Flow
4051S_CA	Ranges 1-4	$\pm 0.10\%$ upper range limit (URL) for 20 years	$\pm 0.15\%$ URL for 20 years	$\pm 0.10\%$ URL for 20 years
4051S_CG	Ranges 2-5			
4051S_CD	Ranges 2-5			
4051S_T	Ranges 1-3	$\pm 0.10\%$ URL for 20 years	$\pm 0.15\%$ URL for 20 years	$\pm 0.10\%$ URL for 20 years

## Warranty

### Note

See Emerson Terms and Conditions of Sale for warranty details.

**Table 6: Warranty**

Models	Ultra and Ultra-For-Flow <sup>(1)</sup>	Classic <sup>(2)</sup>	Optional extended warranty <sup>(3)</sup>
All Rosemount 4051S Products	20-year limited warranty	1-year limited warranty	WR3: 3-year limited warranty WR5: 5-year limited warranty

(1) Rosemount Ultra and Ultra-For-Flow transmitters have a limited warranty of 20 years from date of shipment. All other provisions of Emerson standard limited warranty remain the same.

(2) Goods are warranted for 12 months from the date of initial installation or 18 months from the date of shipment by seller, whichever period expires first.

(3) Rosemount extended warranties have a limited warranty of three or five years from date of shipment.

## Dynamic performance

Figure 1: Transmitter Output vs. Time




Table 7: Total Time Response at 75 °F (24 °C), Includes Dead Time

	4051S_C 4051SF	4051S_T
Standard	Differential pressure (DP) Ranges 2-5: 80 ms Range 1: 230 ms Range 0: 340 ms Range U: 80 ms	80 ms
High-speed time response (option P6)	DP Ranges 2-3: 40 ms	N/A

### Note

Consult [DP Level Sizing and Selection](#) for transmitter configurations with remote seals, including Rosemount 4051SLT.

Table 8: Dead Time

Response time option	4051S_C 4051S_T 4051SF 4051SLT
Standard	40 ms
High-speed time response (option P6)	20 ms

Table 9: Sensor Update Rate

Response Time Option	4051S_C 4051S_T 4051SF 4051SLT
Standard	48 updates per second
High-speed time response (option P6)	167 updates per second

## Ambient temperature effect

**Table 10: Ambient temperature effect**

Model(s)	Range(s)	Ultra [per 50 °F (28 °C)]	Classic [(per 50 °F (28 °C)]	Ultra-For-Flow
4051S_CD 4051S_CG	0	$\pm(0.25\%$ upper range limit (URL) + 0.05% span) from 1:1 to 30:1	$\pm(0.25\%$ URL + 0.05% span) from 1:1 to 30:1	N/A
	1	$\pm(0.1\%$ URL + 0.25% span) from 1:1 to 50:1	$\pm(0.1\%$ URL + 0.25% span) from 1:1 to 50:1	N/A
	2–5	$\pm(0.009\%$ URL + 0.025% span) from 1:1 to 10:1 $\pm(0.018\%$ URL + 0.08% span) from > 10:1 to 200:1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 150:1	$\pm 0.13\%$ reading $\leq$ 8:1 differential pressure (DP) turndown from URL $\pm (0.0187\%$ URL + 0.13% reading) > 8:1 and $\leq$ 100:1 DP turndown from URL
	U	$\pm(0.009\%$ URL + 0.025% span) from 1:1 to 10:1 $\pm(0.018\%$ URL + 0.08% span) from > 10:1 to 200:1 $\pm(0.0024\%$ URL + 3.205% span) from > 200:1 to 800:1	N/A	$\pm 0.13\%$ reading $\leq$ 8:1 DP turndown from URL $\pm(0.0187\%$ URL + 0.13% reading) > 8:1 and $\leq$ 100:1 DP turndown from URL +/- (0.005% URL + 1% reading) > 100:1 and $\leq$ 800:1 DP turndown from URL
4051S_T	1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 100:1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 100:1	N/A
	2–4	$\pm(0.009\%$ URL + 0.025% span) from 1:1 to 10:1 $\pm(0.018\%$ URL + 0.08% span) from > 10:1 to 200:1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 150:1	
	5	$\pm(0.05\%$ URL + 0.075% span) from 1:1 to 10:1	$\pm(0.05\%$ URL + 0.075% span) from 1:1 to 5:1	
4051S_CA	0	$\pm(0.1\%$ URL + 0.25% span) from 1:1 to 30:1	$\pm(0.1\%$ URL + 0.25% span) from 1:1 to 30:1	N/A
	1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 100:1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 100:1	
	2–4	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 200:1	$\pm(0.0125\%$ URL + 0.0625% span) from 1:1 to 5:1 $\pm(0.025\%$ URL + 0.125% span) from > 5:1 to 150:1	

### Ambient temperature effect for liquid level transmitter

For Rosemount 4051SLT, see [DP Level Sizing and Selection](#).

## Line pressure effect

**Table 11: Line Pressure Effect**

Rosemount 4051S_CD 4051SF (differential pressure [DP] measurement only)	Ultra and Ultra-For-Flow	Classic
<b>Zero error<sup>(1)</sup></b>		
Range 2-3	± 0.025% upper range limit (URL) per 1,000 psi (68.95 bar)	± 0.05% URL per 1,000 psi (68.95 bar)
Range U	± 0.0125% URL per 1,000 psi (68.95 bar)	N/A
Range 0	± 0.125% URL per 100 psi (6.89 bar)	± 0.125% URL per 100 psi (6.89 bar)
Range 1	± 0.25% URL per 1,000 psi (68.95 bar)	± 0.25% URL per 1,000 psi (68.95 bar)
<b>Span error<sup>(2)</sup></b>		
Range 2-3	± 0.1% of reading per 1,000 psi (68.95 bar)	± 0.1% of reading per 1,000 psi (68.95 bar)
Range 0	± 0.15% of reading per 100 psi (6.89 bar)	± 0.15% of reading per 100 psi (6.89 bar)
Range 1	± 0.40% of reading per 1,000 psi (68.95 bar)	± 0.40% of reading per 1,000 psi (68.95 bar)

(1) Zero error can be removed by performing a zero trim at line pressure.

(2) Specifications for option code P0 are two times those shown above.

### Mounting position effect

Models	Ultra, Ultra-For-Flow, Classic, and Classic MV
Rosemount 4051S_CD 4051S_CG	Zero shifts up to ±1.25 inH <sub>2</sub> O (3.11 mbar), which can be zeroed span: no effect
4051S_CA or 4051S_T	Zero shifts to ±2.5 inH <sub>2</sub> O (6.22 mbar), which can be zeroed span: no effect
4051SF Differential pressure (DP) Sensor	Zero shifts up to ±1.25 inH <sub>2</sub> O (3.11 mbar), which can be zeroed span: no effect
4051SLT	With liquid level diaphragm in vertical plane, zero shift of up to ±1 inH <sub>2</sub> O (2.49 mbar). With diaphragm in vertical plane, zero shift of up to ±5 inH <sub>2</sub> O (12.43 mbar) plus extension length on extended units. All zero shifts can be zeroed. Span: no effect

### Vibration effect

For housing style code A: Less than ±0.1 percent of upper range limit (URL) when tested per the requirements of IEC61298-3 field or pipeline with high vibration level (10–1,000 Hz, 0.7 mm displacement peak amplitude, 5 g).

For housing style code S or output protocol S: Less than ±0.1 percent of URL when tested per the requirements of IEC61298-3 field with general application or pipeline with low vibration level (10–1,000 Hz, 0.7 mm displacement peak amplitude, 2 g).

### Power supply effect

Less than ±0.005 percent of calibrated span per volt change in voltage at the transmitter terminals.

### Electromagnetic compatibility (EMC)

Meets all industrial environment requirements of EN61326 and NAMUR NE-21. Maximum deviation is less than 1 percent (< 1%) span during EMC disturbance.

#### Note

During surge event, device may exceed maximum EMC deviation limit or reset; however, device will self-recover and return to normal operation within specified start-up time.

## Transient protection

Tested in accordance with the Institute of Electrical and Electronics Engineers (IEEE) C62.41.2-2002, Location Category B

- 6 kV crest, 100 kHz (0.5  $\mu$ s)
- 3 kA crest (8  $\times$  20  $\mu$ s)
- 6 kV crest (1.2  $\times$  50  $\mu$ s)

## External ground screw assembly

**Table 12: External Ground Screw Assembly**

Option code	External ground screw assembly included?
I1, K5, I5, K6, E6, I6, I7, KL	No - Order Option X1
K1, E1, N1, ND, K7, E7, N7, KS	Yes

## Functional specifications

### Range and sensor limits

**Table 13: Transmitter with Coplanar™ Differential and Gauge Sensor Modules**

Range	Minimum span		Sensor limits		
	Ultra	Classic	Upper range limit (URL)	Lower range limit (LRL)	
				4051S_CD <sup>(1)</sup>	4051S_CG <sup>(2)</sup>
0	0.1 inH <sub>2</sub> O (0.25 mbar)	0.1 inH <sub>2</sub> O (0.25 mbar)	3.0 inH <sub>2</sub> O (7.46 mbar)	-3.0 inH <sub>2</sub> O (-7.46 mbar)	N/A
1	0.5 inH <sub>2</sub> O (1.24 mbar)	0.5 inH <sub>2</sub> O (1.24 mbar)	25 inH <sub>2</sub> O (62.16 mbar)	-25 inH <sub>2</sub> O (-62.16 mbar)	-25 inH <sub>2</sub> O (-62.16 mbar)
2	1.25 inH <sub>2</sub> O (3.11 mbar)	1.67 inH <sub>2</sub> O (4.14 mbar)	250 inH <sub>2</sub> O (621.6 mbar)	-250 inH <sub>2</sub> O (-621.6 mbar)	-250 inH <sub>2</sub> O (-621.6 mbar)
3	5.0 inH <sub>2</sub> O (12.43 mbar)	6.67 inH <sub>2</sub> O (16.58 mbar)	1,000 inH <sub>2</sub> O (2.49 bar)	-1,000 inH <sub>2</sub> O (-2.49 bar)	0.5 psia (34.47 mbar)
4	1.5 psi (103.42 mbar)	2.0 psi (137.9 mbar)	300 psi (20.68 bar)	-300 psi (-20.7 bar)	0.5 psia (34.47 mbar)
5	10.0 psi (689.48 mbar)	13.33 psi (919.3 mbar)	2,000 psi (137.9 bar)	-2,000 psi (-137.9 bar)	0.5 psia (34.47 mbar)
U	1.25 inH <sub>2</sub> O (3.11 mbar)	1.25 inH <sub>2</sub> O (3.11 mbar)	1,000 inH <sub>2</sub> O (2.49 bar)	-1,000 inH <sub>2</sub> O (-2.49 bar)	N/A

(1) The Lower Range Limit (LRL) is 0 inH<sub>2</sub>O (0 mbar) for Ultra-For-Flow Performance Class and Rosemount 4051SF Flow Meters.

(2) Assumes atmospheric pressure of 14.7 psia (1 bar).

**Table 14: Transmitter with In-Line Sensor Modules**

Range	Minimum span		Sensor limits		
	Ultra	Classic	Upper (URL)	Lower (LRL)	
				Absolute <sup>(1)</sup>	Gauge
1	0.3 psi (20.68 mbar)	0.3 psi (20.68 mbar)	30 psi (2.07 bar)	0 psia (0 bar)	-14.7 psig (-1.01 bar)

**Table 14: Transmitter with In-Line Sensor Modules (continued)**

Range	Minimum span		Sensor limits		
	Ultra	Classic	Upper (URL)	Lower (LRL)	
				Absolute <sup>(1)</sup>	Gauge
2	0.75 psi (51.71 mbar)	1.0 psi (68.95 mbar)	150 psi (10.34 bar)	0 psia (0 bar)	-14.7 psig (-1.01 bar)
3	4.0 psi (275.79 mbar)	5.33 psi (367.72 mbar)	800 psi (55.16 bar)	0 psia (0 bar)	-14.7 psig (-1.01 bar)
4	20 psi (1.38 bar)	26.67 psi (1.84 bar)	4,000 psi (275.79 bar)	0 psia (0 bar)	-14.7 psig (-1.01 bar)
5 <sup>(2)</sup>	1,000 psi (68.95 bar)	2,000 psi (137.9 bar)	1,0000 psi (689.48 bar)	0 psia (0 bar)	-14.7 psig (-1.01 bar)

- (1) Assumes atmospheric pressure of 14.7 psia (1 bar-a).
- (2) Range 5 gauge is offered as a sealed gauge only using the absolute sensor.

**Table 15: Transmitter with Coplanar Absolute Sensor Modules**

Range	Minimum Span		Sensor limits	
	Ultra	Classic	Upper (URL)	Lower (LRL)
0	0.167 psia (11.49 mbar)	0.167 psia (11.49 mbar)	5.0 psia (0.34 bar)	0 psia (0 bar)
1	0.3 psia (20.68 mbar)	0.3 psia (20.68 mbar)	30 psia (2.07 bar)	0 psia (0 bar)
2	0.75 psia (68.95 mbar)	1.0 psia (68.95 mbar)	150 psia (10.34 bar)	0 psia (0 bar)
3	4.0 psia (275.79 mbar)	5.33 psia (367.72 mbar)	800 psia (55.16 bar)	0 psia (0 bar)
4	20 psia (1.38 bar)	26.67 psia (1.84 bar)	4000 psia (275.79 bar)	0 psia (0 bar)

## 4-20 mA HART® protocol

### Zero and span adjustment

Zero and span values can be set anywhere within the range. Span must be greater than or equal to the minimum span.

### Output

The 2-wire 4-20 mA is user-selectable for linear or square root output. Digital process variable superimposed on 4-20 mA signal is available to any host that conforms to the HART® protocol.

### Power supply


External power supply required. Standard transmitter (4-20 mA) operates on 11.5 to 42.4 Vdc with no load.

### Load limitations

Maximum loop resistance is determined by the voltage level of the external power supply described by:

$$\text{Maximum loop resistance} = 42.37 \times (\text{power supply voltage} - 11.5)$$

Communication requires a minimum loop resistance of 250 Ω.



- A. Load (ohms)
- B. Operating region
- C. Voltage (Vdc)

### Indication

The graphical backlit LCD display provides a 128 x 128 pixel display with a backlight. You can enable or disable the display via HART. The LCD display module can be rotated via software controls but cannot be repositioned physically on the unit.

The display also functions as a local operator interface (LOI), with two configuration buttons provided for the user to navigate menus.

The display also has a number of additional configuration parameters that can be set up: Add a gauge pressure/ absolute pressure (GP/AP) unit label, setting of the decimal separator between either a comma or period, ability to customize the number of significant digits shown, and set the display language. The languages include:

- English
- Chinese
- French
- German
- Italian
- Portuguese
- Spanish

The remote digital display includes a 4-wire communication cable that carries signal and power lines between the two terminal blocks in the remote meter system.

### Configuration buttons

Quick service buttons included with the digital display allow for straightforward commissioning using a simple menu underneath the housing cover. The quick service buttons allow users to zero, re-range their device, perform a loop test, view configuration, and rotate the graphical LCD display screen in the field.

Analog zero and span included with the digital display changes analog value and can be used to re-range the transmitter with an applied pressure.

### Bluetooth® connectivity

Typical range: At least 50 ft. (15 m) line of sight. Maximum communication range will vary depending on orientation, obstacles (person, metal, wall, etc.), or electromagnetic environment.

### Advanced diagnostics

Advanced diagnostics on the Rosemount 4051S provide complete coverage from the process to control room.

The diagnostic capabilities progressively enhance from option A to option B, culminating in the most advanced features available in option C.

The **Loop Integrity** diagnostic proactively detects and notifies you of changes in the electrical loop before they affect your process operation. Example loop problems that can be detected include corrosion of terminals, water in the terminal compartment, and unstable power supplies.

The **Enhanced SIS and proof testing** capability provides improved usability when performing partial and comprehensive proof tests. The user interface of the transmitter includes guided methods to make performing proof tests quick and easy. In addition, the in-situ partial proof test provides expanded partial proof test coverage without the need for an external pressure source. Proof test logs are also included so historical information can be accessed at any time.

The **Plugged Impulse Line** diagnostic uses statistical processing technology to detect plugging in impulse piping that may prevent the transmitter from obtaining an accurate process reading. It can also detect and alert you to other process connection issues, such as plugged Annubar™ or orifice plate process taps.

The **Process Intelligence** diagnostic also uses statistical processing technology by monitoring the standard deviation and coefficient of variation which can then be used to detect process and process equipment anomalies including but not limited to:

- Furnace flame instability
- Pump cavitation
- Distillation column flooding
- Fluid composition change
- Entrained air
- Agitation loss
- Process leak

Option Code A includes:	Option Code B includes:	Option Code C includes:
<ul style="list-style-type: none"> <li>▪ Basic transmitter diagnostics</li> <li>▪ Loop integrity</li> <li>▪ Logging capabilities</li> </ul>	<ul style="list-style-type: none"> <li>▪ Basic transmitter diagnostics</li> <li>▪ Loop integrity</li> <li>▪ Logging capabilities</li> <li>▪ Enhanced SIS proof testing with in-situ</li> </ul>	<ul style="list-style-type: none"> <li>▪ Basic transmitter diagnostics</li> <li>▪ Loop integrity</li> <li>▪ Logging capabilities</li> <li>▪ Enhanced SIS proof testing with in-situ</li> <li>▪ Process intelligence</li> <li>▪ Plugged impulse line</li> </ul>

### Relay switch functionality (available with output protocol code S)

The 4051S Pressure Transmitter supports two integral high voltage, high current double pole changeover (DPCO) switches connected directly to the transmitter.

An integral relay switch takes the traditional pressure relay switch and embeds it into the transmitter. On the 4051S, the relay switches are located in the transmitter terminal block (transient protection included). The relays are controlled by the transmitter measurement and are configured using the process alert functionality.

### Relay power

**Note**

The relay switches must be powered by a separate supply from the transmitter power.

As shown in [Figure 2](#), there are separate dedicated terminals for the relay power. The power supplied to the relays must be able to sufficiently drive the electromechanical relay coils of both switches to activate them. If using DC power, the terminals are polarity sensitive. If using AC power, there is no polarity sensitivity.

- Transmitter power is 11.5 to 42.4 Vdc.
- Relay power voltage is 21.5 to 60 Vdc or 20 to 264 Vac, 50.60 Hz.
- Relay power current is 5 A maximum resistive load, 3.5 A maximum inductive load.

Table 16 shows the Relay 1 and Relay 2 load power requirements.


**Table 16: Relay Power**

Parameter		Resistive load	Inductive load
cos $\phi$		1	0.4
L/R		0 ms	7 ms
$I_{MAX}$		5 A	3.5 A
$U_{MAX}$	ac	250 V	250 V
$U_{MAX}$	dc	30 V	30 V
$O_{MAX}$	ac	1,250 VA	875 VA
$O_{MAX}$	dc	240 W	170 W

**⚠ WARNING**

A double pole, single throw (DPST) On/Off switch must be fitted for safe disconnection of the power supply. Fit the DPST switch as near as possible to the pressure relay switch. Keep the DPST switch free of obstructions. Label the DPST switch to indicate it is the supply disconnection device for the power relay switch.

**Figure 2: Relay Switches**



**Overpressure limits**

Transmitters withstand the following limits without damage:

**Table 17: Maximum Overpressure Limits**

The pressure that can be applied to the process input (single side) without damage to the transmitter.

Range	4051S_TG/4051S_TA	4051S_CA	4051S_CG	4051S_CD <sup>(1)</sup>
0	N/A	60 psia (4.1 bar)	N/A	750 psi (51.7 bar)
1	750 psi (51.7 bar)	750 psi (51.7 bar)	2,000 psi (137.9 bar)	2,000 psi (137.9 bar)
2	1,500 psi (103.4 bar)	1,500 psi (103.4 bar)	3,626 psi (250.0 bar)	3,626 psi (250.0 bar)
3	1,600 psi (110.3 bar)	1,600 psi (110.3 bar)	3,626 psi (250.0 bar)	3,626 psi (250.0 bar)
4	6,000 psi (413.7 bar)	6,000 psi (413.7 bar)	3,626 psi (250.0 bar)	3,626 psi (250.0 bar)
5	15,000 psi (1034.2 bar)	N/A	3,626 psi (250.0 bar)	3,626 psi (250.0 bar)
U	N/A	N/A	2,000 psi (137.9 bar)	2,000 psi (137.9 bar)

(1) The overpressure limit of a differential pressure (DP) Sensor with the P0 option is 6,170 psig (425.4 bar).

**Liquid level transmitter (Rosemount 4051SLT)**

Overpressure limit is dependent on the flange rating or sensor rating (whichever is lower). Use the [DP Level Sizing and Selection Tool](#) to ensure the seal system meets all pressure and temperature limits.

**Static pressure limits**

**Table 18: Static Pressure Limits**

Operates within specifications between static line pressures of:

Range	Rosemount 4051S_CD <sup>(1)</sup>
0	0.5 psia to 750 psig (0.03 bar to 51.71 bar)
1	0.5 psia to 2,000 psig (0.03 bar to 137.90 bar)
2	0.5 psia to 3,626 psig (0.03 bar to 250.00 bar)
3	0.5 psia to 3,626 psig (0.03 bar to 250.00 bar)
4	0.5 psia to 3,626 psig (0.03 bar to 250.00 bar)
5	0.5 psia to 3,626 psig (0.03 bar to 250.00 bar)
U	0.5 psia to 2,000 psig (0.03 bar to 137.90 bar)

(1) The static pressure limit of a differential pressure (DP) Sensor with the P0 option is 6,170 psig (425.4 bar).

**Maximum working pressure limits**

Maximum working pressure is the maximum pressure allowed for normal transmitter operation. For a differential pressure transmitter, the maximum working pressure is the static line pressure under which the transmitter can safely operate.

If one side of the transmitter is exposed to the full static line pressure due to mis-valving, the transmitter will experience an output shift and must be re-zeroed.

For a gauge or absolute pressure transmitter, the maximum working pressure is the same as the Upper Range Limit (URL).

The maximum working pressure of transmitters with assemble-to options is limited by the lowest maximum pressure rating of the individual components.

**Table 19: Rosemount 4051S Maximum Working Pressure**

Range	TG/TA	CA	CG	CD
0	N/A	5 psia (0.34 bar)	N/A	750 psi (51.7 bar)
1	30 psi (2.1 bar)	30 psi (2.1 bar)	25 inH <sub>2</sub> O (62.2 mbar)	2,000 psi (137.9 bar)
2	150 psi (10.3 bar)	150 psi (10.3 bar)	250 inH <sub>2</sub> O (621.6 mbar)	3,626 psi (250.0 bar)

**Table 19: Rosemount 4051S Maximum Working Pressure (continued)**

Range	TG/TA	CA	CG	CD
3	800 psi (55.2 bar)	800 psi (55.2 bar)	1,000 inH <sub>2</sub> O (2.5 bar)	3,626 psi (250.0 bar)
4	4,000 psi (275.8 bar)	4,000 psi (275.8 bar)	300 psi (20.7 bar)	3,626 psi (250.0 bar)
5	10,000 psi (689.5 bar)	N/A	2,000 psi (137.9 bar)	3,626 psi (250.0 bar)
U	N/A	N/A	2,000 psi (137.9 bar)	2,000 psi (137.9 bar)

## Burst pressure limits

### Coplanar™ sensor module (4051S\_C, 4051SF, 4051SLT\_G, or A)

10,000 psig (689.47 bar)

### Differential pressure (DP) range 2-4, static pressure range 5

16,400 psi (1,130.74 bar)

### In-line sensor module (4051S\_T, 4051SLT)

- Ranges 1–4: 11,000 psi (758.42 bar)
- Range 5: 26,000 psi (1792.64 bar)

## Temperature limits

### Ambient

-40 to +185 °F (-40 to +85 °C)

With display<sup>(1)</sup>: -40 to 185 °F (-40 to 85 °C)

With option code P0: -20 to 185 °F (-28 to 85 °C)

With option code BR6: -76 to 185 °F (-60 to 85 °C)

### Storage

-50 to 185 °F (-46 to 85 °C)

With display: -40 to 185 °F (-40 to 85 °C)

With option code BR6: -76 to 185 °F (-60 to 85 °C)

**Table 20: Process Temperature Limits**

At atmospheric pressures and above:

Coplanar™ sensor module 4051S_C, 4051SF	
Silicone fill sensor	N/A
with Coplanar flange <sup>(1)</sup>	-40 to 250 °F (-40 to 121 °C) <sup>(2)</sup>
with traditional flange <sup>(3)</sup>	-40 to 300 °F (-40 to 149 °C) <sup>(2)(4)</sup>
with level flange <sup>(3)</sup>	-40 to 300 °F (-40 to 149 °C) <sup>(2)</sup>
with Rosemount 305 integral manifold <sup>(1)</sup>	-40 to 300 °F (-40 to 149 °C) <sup>(2)(4)</sup>
Inert fill sensor <sup>(1)</sup>	-40 to 185 °F (-40 to 85 °C) <sup>(5)(6)</sup>
with Option Code BR6, Coplanar flange	-76 to 250 °F (-60 to 121 °C) <sup>(2)</sup>

(1) LCD display may not be readable, and LCD updates will be slower at temperatures below -13°F (-25°C).

**Table 20: Process Temperature Limits (continued)**

with Option Code BR6, traditional flange	-75 to 300 °F (-60 to 149 °C) <sup>(2)</sup>
<b>In-line sensor module</b>	
<b>4051S_T</b>	
Silicone fill sensor <sup>(1)</sup>	-40 to 250 °F (-40 to 121 °C) <sup>(2)</sup>
with Option Code BR6	-76 to 250 °F (-60 to 121 °C) <sup>(2)</sup>
Inert fill sensor <sup>(1)</sup>	-22 to 250 °F (-30 to 121 °C) <sup>(2)</sup>
<b>4051SLT Level Transmitter</b>	
Silicone 704 <sup>(7)</sup>	32 to 599 °F (0 to 315 °C)
Silicone 705 <sup>(7)</sup>	68 to 698 °F (20 to 370 °C)
UltraTherm™ 805	770 °F (410 °C) with 850 °F (454 °C) design <sup>(8)</sup>
Silicone 200	-49 to 401 °F (-45 to 205 °C)
Tri-Therm 300	-40 to 401 °F (-40 to 205 °C)
Inert (Halocarbon)	-49 to 320 °F (-45 to 160 °C)
Glycerin and water <sup>(9)(10)</sup>	5 to 203 °F (-15 to 95 °C)
Neobee® M-20 <sup>(9)</sup>	5 to 437 °F (-15 to 225 °C)
Propylene glycol and water <sup>(9)(10)</sup>	5 to 203 °F (-15 to 95 °C)

(1) The maximum ambient temperature is reduced by 1.5 °F for every degree by which the process fluid temperature exceeds 185 °F (85 °C).

(2) 220 °F (104 °C) limit in vacuum service; 130 °F (54 °C) for pressures below 0.5 psia.

(3) The maximum ambient temperature is reduced by 1.0 °F for every degree by which the process fluid temperature exceeds 185 °F (85 °C) for all traditional flanges and vertical mount level flanges.

(4) -20 °F (-29 °C) is the lower process temperature limit with option code P0.

(5) 160 °F (71 °C) limit in vacuum service.

(6) Not available for 3051S\_CA.


(7) Only available with Seal Connection Type/Capillary ID, Description Codes C, D, F, G, J, K, N, and P.

(8) UltraTherm 805 supports a maximum design temperature of 850 °F (454 °C). Design temperature rating is for non-continuous use with a cumulative exposure time less of than 12 hours. Continuous use temperature is rated to 770 °F (410 °C).

(9) This is a food grade fill fluid.

(10) Not suitable for vacuum applications.

### Thermal Range Expander temperature operating range



- ..... Silicone 704
  - Silicone 705
  - UltraTherm 805
- A. Ambient temperature (°C)  
 B. Process temperature (°C)

### Humidity limits

0–100 percent relative humidity

### Turn-on time

When power is applied to the transmitter during startup, performance will be within a maximum turn-on time of 5 seconds.

### Volumetric displacement

For Rosemount 4051SC, it is less than 0.005 in.<sup>3</sup> (0.08 cm<sup>3</sup>).

For 4051ST, it is less than 0.0005 in.<sup>3</sup> (0.008 cm<sup>3</sup>).

### Damping

Analog output response time to a step change is user-selectable from 0 to 60 seconds for one time constant.

### Failure mode alarm

If self-diagnostics detect a gross transmitter failure, the analog signal will be driven offscale to alert the user. Rosemount standard (default), NAMUR, and custom alarm levels are available. (See [Table 21](#)).

High or low alarm signal is software-selectable or hardware-selectable via the optional switch.

**Table 21: Alarm Configuration**

Configuration	High alarm	Low alarm
Default	22.5 mA	3.725 mA
NAMUR compliant <sup>(1)</sup>	22.5 mA	3.575 mA
Custom levels <sup>(2)</sup>	20.2 to 23.0 mA	3.57 to 3.8 mA

(1) Analog output levels are compliant with NAMUR recommendation NE 43, see option codes C4 or C5.

(2) Low alarm must be 0.1 mA less than low saturation and high alarm must be 0.1 mA greater than high saturation.

## NAMUR recommendations

The Rosemount 4051S meets the following NAMUR recommendations:

- NE 21** Electromagnetic compatibility (EMC) for Process and Laboratory Apparatus
- NE 43** Standard on the signal level breakdown information of digital transmitters
- NE 53** Revision controlled labeling for software and hardware changes
- NE 107** Self-Monitoring and Diagnosis of Field Devices

## Physical specifications

### Material selection

Emerson provides a variety of Rosemount products with various product options and configurations, including materials of construction that can be expected to perform well in a wide range of applications.

The product information presented is intended as a guide for the purchaser to make an appropriate selection for the application. It is the purchaser's sole responsibility to make a careful analysis of all process parameters (such as all chemical components, temperature, pressure, flow rate, abrasives, contaminants, etc.), when specifying product, materials, options, and components for the particular application. Emerson is not in a position to evaluate or guarantee the compatibility of the process fluid or other process parameters with the product, options, configuration, or materials of construction selected.

### Electrical connections

½-14 NPT, G½, and M20 × 1½ conduit. HART® interface connections fixed to terminal block.

### Process connections

Coplanar™ sensor module (Rosemount 4051S_C and 4051SF)	
Standard	¼-18 NPT on 2½-in. centers
Flange adapters	½-14 NPT and RC½ on 2 in. (50.8 mm), 2½ in. (54.0 mm), or 2¾ in. (57.2 mm) centers
In-line sensor module (Rosemount 4051S_T)	
½-14 NPT female	
Non-threaded instrument flange (available in SST for sensor ranges 1-4 only)	
G½ A DIN 16288 male (available in SST for sensor ranges 1-4 only)	
Autoclave type F-250C (Pressure relieved 916-18 gland thread; ¼ OD high pressure tube 60° cone; available in SST for sensor range 5 only)	

<b>Level transmitter (Rosemount 4051SLT)</b>
Refer to <a href="#">Process connection size</a> .

## Process-wetted parts

### Process isolating diaphragms

<b>Coplanar™ sensor module (Rosemount 4051S_C)</b>
<ul style="list-style-type: none"> <li>▪ 316L stainless steel (SST) (UNS S31603)</li> <li>▪ Alloy C-276 (UNS N10276)</li> <li>▪ Alloy 400 (UNS N04400)</li> <li>▪ Tantalum (UNS R05440)</li> <li>▪ Gold-Plated Alloy 400</li> <li>▪ Gold-plated 316L SST</li> </ul>
<b>In-line sensor module (4051S_T)</b>
316L SST (UNS S31603), Alloy C-276 (UNS N10276)
<b>Level transmitter (Rosemount 4051SLT)</b>
Refer to <a href="#">Seal diaphragm material</a> .

### Drain/vent valves

316 SST, Alloy C-276, or Alloy 400/K-500 material

(Drain vent seat: Alloy 400, Drain vent stem: Alloy K-500)

#### Note

Alloy 400/K-500 is not available with Rosemount 4051SLT.

### Process flanges and flange adapters

Plated carbon steel

SST: CF-8M (Cast 316 SST) per ASTM A743

Cast C-276: CW-12MW per ASTM A494

Alloy 400: M-30C per ASTM A494

### Wetted O-rings

Glass-filled PTFE

### Rosemount 4051SLT mounting flange

Zinc-cobalt plated CS or 316 SST

### Rosemount 4051SLT seal extension

CF-3M (Cast 316L SST, material per ASTM A743) or CW-12MW (Cast C-276, material per ASTM A494)

## Non-wetted parts

### Electronics housing

Low-copper aluminum alloy or CF-8M (Cast 316 stainless steel [SST])

Enclosures meet Type 4X, IP66, and IP68 [66 ft. (20 m) for 168 hours] when properly installed.

**Coplanar sensor module housing**

SST: CF-3M (Cast 316L SST)

**Bolts**

Plated carbon steel per ASTM A449, Type 1

Austenitic 316 SST per ASTM F593

ASTM A453, Class D, Grade 660 SST

ASTM A193, Grade B7M alloy steel

ASTM A193, Class 2, Grade B8M SST

Alloy K-500

**Sensor module fill fluid**

Silicone is standard.

Inert is available as option code.

**Note**

Inert is not available with Rosemount 4051S\_CA.

Inert for in-line series uses Fluorinert™ FC-43.

Inert for coplanar series uses Halocarbon.

**Seal fill fluid (liquid level only)**

Rosemount 4051SLT: Silicone 200, Tri-Therm 300, Silicone 704, Silicone 705, UltraTherm™ 805, inert, SYLTHERM™ XLT, Neobee® M-20, glycerin and water, propylene glycol and water

**Paint for aluminum housing**

Polyurethane

**Cover O-rings**

Buna-N

**Shipping weights**

**Table 22: Transmitter Weights**

Fully functional transmitter with module, terminal block, standard covers, and connector board, if applicable.

Complete transmitter weights <sup>(1)</sup> (without options)	Weight
Rosemount 4051S_C	6.8 lb. (3.08 kg)
4051S_T	5 lb. (2.27 kg)
4051S_C (stainless steel [SST])	12.3 lb. (5.58 kg)
4051S_T (SST)	10.5 lb. (4.76 kg)

<sup>(1)</sup> These weights do not include the flange.

**Table 23: Optional Item Weights**

Optional item weights	Weight
B1 with U-bolt and bolts	1.71 lb. (0.77 kg)
B2 with U-bolt and bolts	1.282 lb. (0.58 kg)
B3 with U-Bolt and bolts	1.668 lb. (0.76 kg)
B4 (S_C) bracket with U-bolt and bolts	1.186 lb. (0.54 kg)

**Table 23: Optional Item Weights (continued)**

Optional item weights	Weight
B4 (S_C with manifold) with U-bolt and bolts	1.544 lb. (0.70 kg)
B4 (S_T) with U-bolt and bolts	1.322 lb. (0.60 kg)
B7 (B1 with SST U-bolt and bolts)	1.716 lb. (0.78 kg)
B8 (B2 with SST U-bolt and bolts)	1.282 lb. (0.58 kg)
B9 (B3 with SST U-bolt and bolts)	1.676 lb. (0.76 kg)
BA with U-bolt and bolts	1.526 lb. (0.69 kg)
BC with U-bolt and bolts	1.562 lb. (0.71 kg)
SST traditional flange	2.700 lb. (1.23 kg)
SST traditional flange with carbon steel mounting bolts	3.052 lb. (1.384 kg)
SST traditional flange with SST mounting bolts	3.056 lb. (1.39 kg)
DP – Alloy C-276 drain/vent (x2)	0.196 lb. (0.09 kg)
DP – SST drain/vent (x2)	0.176 lb. (0.08 kg)
GP – SST drain/vent (x1) and SST plug (x2)	0.116 lb. (0.05 kg)
GP – Alloy C-276 drain/vent (x1) and SST plug (x2)	0.128 lb. (0.06 kg)
Traditional flange (Alloy C-276)	3.034 lb. (1.38 kg)
SST coplanar flange with carbon steel mounting bolts	1.722 lb. (0.78 kg)
SST coplanar flange with SST mounting bolts	1.726 lb. (0.78 kg)
Traditional flange (Alloy 400)	3.010 lb. (1.37 kg)
Traditional flange (SST with 2 Alloy C-276 D/V)	2.896 lb. (1.31 kg)
Level flange – 3 in., Class 150	12.618 lb. (5.72 kg)
Level flange – 3 in., Class 300	15.920 lb. (7.22 kg)
Level flange – 2 in., Class 150	6.772 lb. (3.07 kg)
Level flange – 2 in., Class 300	8.248 lb. (3.74 kg)
DIN Level flange, SST, DN 50, PN 40	7.818 lb. (3.55 kg)
DIN Level flange, SST, DN 80, PN 40	12.950 lb. (5.87 kg)

**Table 24: Individual Item Weights**

Individual item weights	Weight
Aluminum standard cover	0.53 lb. (0.24 kg)
SST standard cover	1.53 lb. (0.69 kg)
Aluminum meter cover assembly	0.88 lb. (0.40 kg)
SST meter cover assembly	2.11 lb. (0.97 kg)
LCD with screws	0.16 lb. (0.07 kg)
Terminal block	0.15 lb. (0.07 kg)
Output board/feature board (no screws)	0.14 lb. (0.06 kg)
Housing, Aluminum	1.52 lb. (0.69 kg)
Housing, SST	4.56 lb. (2.07 kg)
Top tag, Aluminum	0.006 lb. (0.003 kg)

**Table 24: Individual Item Weights (continued)**

Individual item weights	Weight
Top tag, SST	0.025 lb. (0.011 kg)
Wrap-around nameplate	0.056 lb. (0.025 kg)
Housing with electronics only	3.67 lb. (1.664 kg)







For more information: [Emerson.com/global](https://emerson.com/global)

©2025 Emerson. All rights reserved.

Emerson Terms and Conditions of Sale are available upon request. The Emerson logo is a trademark and service mark of Emerson Electric Co. Rosemount is a mark of one of the Emerson family of companies. All other marks are the property of their respective owners.

The "Bluetooth" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Emerson is under license.